

Hewlett Packard Enterprise ProLiant DL580 server (793310-B21)

Intel Xeon E7-4850 v3 (35M Cache, 2.20 GHz), 8 x 16GB, SFF SAS, 1200W, 4U



Price details:

Price excl. VAT: 28,066.08 €

Eco fees: 0.00 €

VAT 21 %: 5,893.88 €

Product details:

Product code: 793310-B21

EAN: 0888793733622

Manufacturer: Hewlett Packard Enterprise

33,959.96 €

* VAT included

PDF generated on: 11 December, 2017



Does your business demand fast insights, support for increased number of users and uncompromised availability?

The HP ProLiant DL580 Gen9 Server is the HP four socket (4S) enterprise standard x86 server offering commanding performance, rock-solid reliability and availability, and compelling consolidation and virtualization efficiencies.

Supporting Intel® Xeon® E7-4800/8800 v3 processors, the DL580 Gen9 Server offers enhanced processor performance, up to 6 TBs of memory, greater IO bandwidth (9 PCIe Gen 3.0 slots), and 12 Gb/s of SAS speeds. The DL580 Gen9 Server has security and data protection features for system resiliency that your business can depend on. All, making it ideal for mission-critical enterprise, business intelligence, and database applications.

Whether needed for highly virtualized or cloud based deployments, with intelligence and simplicity of automated management with HP OneView and HP iLO 4 your business can achieve agile and lower cost infrastructure management.

Main specifications:

Processor

Processor frequency:	2.2 GHz
Processor family:	Intel Xeon E7 v3
Processor model:	E7-4850V3
Processor cores:	14
Processor cache type:	Last Level Cache
Processor cache:	35 MB
System bus rate:	8 GT/s
Processor socket:	LGA 2011 (Socket R)
Processor boost frequency:	2.8 GHz
Processor lithography:	22 nm
Processor threads:	28
Processor operating modes:	64-bit
Stepping:	E0
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	3
Processor codename:	Haswell
Tcase:	70 °C
Maximum internal memory supported by processor:	1536 GB
Memory types supported by processor:	DDR4-SDRAM,DDR3-SDRAM
Memory clock speeds supported by processor:	1333,1600,1800,1066 MHz
Memory bandwidth supported by processor (max):	102 GB/s

Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	32
PCI Express configurations:	x4, x8, x16
Processor package size:	52 mm
Supported instruction sets:	AVX 2.0
Processor code:	SR221
Scalability:	S4S
Physical Address Extension (PAE):	Y
Physical Address Extension (PAE):	46 bit
Embedded options available:	N
Thermal Design Power (TDP):	115 W
Processor series:	Intel Xeon E7-4800 v3
Conflict Free processor:	Y

Memory

Internal memory:	128 GB
Internal memory type:	DDR4-SDRAM
Memory slots:	48 DIMM
Memory layout (slots x size):	8 x 16 GB

Storage

Supported storage drive interfaces:	SAS
-------------------------------------	-----

Graphics

On-board graphics adapter:	N
On-board graphics adapter model:	Not available

Networking

Ethernet LAN:	Y
Ethernet interface type:	10 Gigabit Ethernet

Expansion slots

PCI Express slots version:	3.0
----------------------------	-----

Design

Chassis type:	Rack (4U)
Optical drive type:	N

Processor special features

CPU configuration (max):	4
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	N
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	N
Intel® Smart Cache:	N
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	N
Intel® Secure Key:	Y
Intel TSX-NI:	Y
Intel® OS Guard:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	N
Intel 64:	Y
Intel Instruction Replay Technology:	N

Intel Instruction Replay Technology version:	0.00
Intel Secure Key Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	1.00
Intel Dual Display Capable Technology:	N
Intel HD Graphics:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	84679

Power

Redundant power supply (RPS) support:	Y
Power supply:	4800 W
Number of main power supplies:	4

Weight & dimensions

Width:	444 mm
Depth:	736 mm
Height:	175 mm
Weight:	52800 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.