

Hewlett Packard Enterprise ProLiant BL460c G7 server (603588R-B21)

Intel Xeon E5620 (2.4GHz, 12MB L3), 6GB DDR3, Smart Array P410i/Zero, Blade



Price details:

Price excl. VAT: 1,620.03 €

Eco fees: 0.00 €

VAT 21 %: 340.21 €

Product details:

Product code: 603588R-B21

EAN: 0886111320523

Manufacturer: Hewlett Packard Enterprise

1,960.24 €

* VAT included

PDF generated on: 19 October, 2017



As the world's most popular blade, the HP ProLiant BL460c G7 Server offers the ideal balance of performance, scalability, and expandability to make it the standard for data center computing. Packing two processors, two hot plug hard drives, up to 384 GB of memory, and a dual-port FlexFabric adapter into a half-height blade, the BL460c gives IT managers a single platform that can handle any business applications.

Features

Dense Compute Power

- Up to two (2) two-, four-, or six-core Intel® Xeon® 5500 or 5600 series processors
- 12 DIMM slots supporting up to 384 GB of DDR-3 memory with Advanced ECC
- HP Smart Array P410i controller for hardware RAID 0 and 1, with optional cache modules for increased performance
- Up to two (2) hot plug small form factor (SFF) SAS, SATA, or SSD drives
- Internal USB and SD card slots enable simple, flexible hypervisor deployments

Integrated HP Virtual Connect FlexFabric Support

- Embedded dual-port 10 Gb FlexFabric adapter delivers high bandwidth for network intensive applications
- Simplify management and lower infrastructure costs by converging LAN and SAN traffic over the same flexible connection
- Up to eight (8) connections to network and storage without the need for add-in mezzanine cards
- Divide and fine-tune network and storage bandwidth to match application requirements

Industry-leading Infrastructure Management

- Save time and conserve valuable IT resources by simplifying remote management with HP Integrated Lights-Out 3 (iLO 3)
- Deploy servers quickly, proactively manage virtual or physical server health, and optimize power consumption with HP Insight Control
- Rapidly provision, continuously analyze, and confidently optimize your converged server infrastructure with HP Insight Dynamics

Main specifications:

Processor

Processor frequency:	2.4 GHz
Processor family:	Intel Xeon 5000
Processor model:	E5620
Processor cores:	4
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	12 MB

System bus rate:	5.86 GT/s
Processor manufacturer:	Intel
Processor socket:	Socket B (LGA 1366)
Motherboard chipset:	Intel 5520
Processor boost frequency:	2.66 GHz
Processor lithography:	32 nm
Processor threads:	8
Processor operating modes:	64-bit
Stepping:	B1
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Westmere EP
Tcase:	77.6 °C
Maximum internal memory supported by processor:	384 GB
Memory types supported by processor:	DDR3 800/1066
Memory clock speeds supported by processor:	800,1066 MHz
Memory bandwidth supported by processor (max):	25.6 GB/s
Memory channels supported by processor:	3
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	N
Processor package size:	42.5 mm
Supported instruction sets:	SSE4.2
Processor code:	SLBV4
Physical Address Extension (PAE):	40 bit
Embedded options available:	Y
Thermal Design Power (TDP):	80 W
CPU multiplier (bus/core ratio):	18
Processor series:	Intel Xeon 5600 series
Conflict Free processor:	N

Memory

Internal memory:	6 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	384 GB
Memory slots:	12 DIMM
Memory clock speed:	1333 MHz
ECC:	Y
Memory layout (slots x size):	3 x 2 GB

Storage

Hard drive size:	2.5 "
Hard drive interface:	Serial ATA,Serial Attached SCSI (SAS)
RAID support:	Y
Maximum storage capacity:	2 TB
RAID levels:	0,1
Number of hard drives supported:	2
Hot-swap:	Y

Networking

Ethernet LAN:	Y
Networking features:	10Gb Ethernet

Ports & interfaces

Ethernet LAN (RJ-45) ports:	2
-----------------------------	---

Expansion slots

PCI Express x8 slots:	2
-----------------------	---

Design

Chassis type:	Blade
Optical drive type:	N

Performance

Operating system installed:	N
Compatible operating systems:	Microsoft Windows ServerRed Hat Enterprise Linux (RHEL)SUSE Linux Enterprise Server (SLES)Oracle SolarisVMwareCitrix XenServer

Processor special features

CPU configuration (max):	2
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	Y
Intel® vPro® Technology:	N
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	N
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	Y
Intel 64:	Y
Intel Virtualization Technology (VT-x):	1
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	47925

Power

Redundant power supply (RPS) support:	N
---------------------------------------	---

Weight & dimensions

Width:	55.6 mm
Depth:	509.5 mm
Height:	181.7 mm
Weight:	5220 g

Other features

Disk array controller:	Smart Array P410i/Zero
Graphics adapter:	G200
Graphics adapter family:	Matrox

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.