

Honeywell Thor VM2 tablet (VM2C1A1A1BET01A)

Thor VM2, 24.638 cm (9.7 ") 1024 x 768 Industrial touch panel with resistive touch, Intel Atom Z530, Intel GMA 500, 1GB DDR2, 802.11a/b/g, Bluetooth 2.0+EDR, External WLAN Antenna Connections, Windows CE 6.0, ETSI



Price details:

Price excl. VAT: 1,932.11 €

Eco fees: 0.00 €

VAT 21 %: 405.74 €

Product details:

Product code: VM2C1A1A1BET01A

EAN:

Manufacturer: Honeywell

2,337.85 €

* VAT included

PDF generated on: 22 February, 2018

Thor VM2 Vehicle-Mount Computer Features and Benefits.

Smart Dock: Enables mounting and removal in seconds like a laptop dock but with the ruggedness and sealing required for industrial applications; maximizes efficiency by dynamically shifting workers and computers as the workload changes, while minimizing maintenance cost by enabling a computer to be shifted from one vehicle to another in 1/6 the standard time.

Field-Replaceable Front Panel: Reduces capital and maintenance cost by integrating the two most wear and abuse prone components, the keyboard and touchscreen, into a user-replaceable part; reduces capital costs by substituting spare front panels for spare computers.

Ignition Control: Eliminates the maintenance expense and lost productivity caused by a dead vehicle battery; unit can be configured to automatically go into standby or hibernate at a selectable time after the ignition switch is turned off, saving time for associates while eliminating a point of concern for warehouse management.

Main specifications:

Display

Display diagonal:	9.7 "
Display resolution:	1024 x 768 pixels
LED backlight:	Y
Touchscreen:	Y
Touchscreen type:	Resistive

Processor

Processor frequency:	1.6 GHz
Processor family:	Intel Atom
Processor model:	Z530
Processor cores:	1
Processor cache:	0.512 MB
Processor front side bus:	533 MHz
Bus type:	FSB
Conflict Free processor:	N
CPU multiplier (bus/core ratio):	12
FSB Parity:	N
Processing Die size:	26 mm ²
Processor cache type:	L2
Processor code:	SLB6P
Processor codename:	Silverthorne

Processor lithography:	45 nm
Processor operating modes:	32-bit
Processor package size:	13 mm
Processor threads:	2
Scenario Design Power (SDP):	0.96 W
Stepping:	C0
Supported instruction sets:	SSE2,SSE3,SSSE3
Tjunction:	90 °C
Thermal Design Power (TDP):	2 W
Thermal Monitoring Technologies:	Y
Number of Processing Die Transistors:	47 M
Processor ARK ID:	35463
Memory	
Internal memory:	1 GB
Internal memory type:	DDR2-SDRAM
Storage	
Internal storage capacity:	1 GB
Card reader integrated:	Y
Compatible memory cards:	SD
Graphics	
Graphics adapter family:	Intel
Graphics adapter:	GMA 500
Audio	
Built-in speaker(s):	Y
Built-in microphone:	Y
Number of built-in speakers:	2
Camera	
Rear camera:	N
Front camera:	N
Video recording:	N
Networking	
3G:	N
Bluetooth:	Y
Top Wi-Fi standard:	IEEE 802.11g
4G:	N
Wi-Fi standards:	IEEE 802.11a,IEEE 802.11b,IEEE 802.11g
Bluetooth version:	2.0+EDR
WWAN:	O
Ports & interfaces	
Microphone in:	N
Headphone out:	Y
USB 2.0 ports quantity:	1
Mobile High-Definition Link (MHL):	N
Serial ports quantity:	2
DC-in jack:	Y
Design	
Form factor:	Slate
Colour of product:	Black,Grey
Device type:	Full-size tablet
Protection features:	Dust resistant,Scratch resistant,Shock resistant,Water resistant
Performance	
Position location:	N
GPS (satellite):	N
Software	
Platform:	Windows
Operating system installed:	Windows CE
Operating system version:	6.0
Bundled software:	Microsoft Internet Explorer 6, DCWedge
Processor special features	
Intel® Turbo Boost Technology:	N
Intel® Hyper Threading Technology (Intel® HTTechnology):	

Enhanced Intel SpeedStep Technology:	Y
Embedded options available:	Y
Execute Disable Bit:	Y
Idle States:	Y
Intel 64:	N
Intel Enhanced Halt State:	Y
Intel Trusted Execution Technology:	N
Intel Virtualization Technology (VT-x):	Y
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel Demand Based Switching:	Y

Battery

Battery technology:	Lithium-Ion (Li-Ion)
---------------------	----------------------

Weight & dimensions

Width:	268 mm
Depth:	53 mm
Height:	214 mm
Weight:	2200 g

Operational conditions

Operating temperature (T-T):	-20 - 50 °C
Storage temperature (T-T):	-20 - 50 °C
Operating relative humidity (H-H):	5 - 95 %
Storage relative humidity (H-H):	5 - 95 %

Packaging content

Quick start guide:	Y
Keyboard included:	N

Other features

Processor socket:	PBGA441
Wi-Fi:	Y
Dustproof:	Y
Waterproof:	Y
Intel® Virtualization Technology (Intel® VT):	VT-x

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.