

Intermec CV30 POS terminal (CV30A0F1100803)

Windows Mobile 5.0 Premium Edition, 128MB SDRAM, Intel XScale PXA270, 520MHz, 16.256 cm (6.4 ") 640x480, WLAN, Bluetooth, 2 x serial ports, 2 x USB 2.0, 1 x LAN, 2.5mm stereo jack, SD Memory Card



Price details:

Price excl. VAT: 2,099.13 €

Eco fees: 0.30 €

VAT 21 %: 440.88 €

Product details:

Product code: CV30A0F1100803

EAN:

Manufacturer: Intermec

PDF generated on: 12 December, 2017



2,540.31 €

* VAT included

The CV30 from Intermec is a tough fixed mount computer that is equipped to offer high performance capabilities and flexibility of function. The compact computer is ideal for a mobile work force and provides real time supply chain management at the point where data can be collected, that is, at the shop floor, in the warehouse and so on. It is meant for greater efficiency in functions, improved performance and productivity in a more secure environment. Its rugged design helps to face the tough industrial environment, and its magnesium housing display ensures protection from external pollutants like dust, moisture and extreme temperatures.

Main specifications:

Display

Display diagonal:	6.4 "
Display resolution:	640 x 480 pixels
Touchscreen:	Y
Viewing angle, horizontal:	140 °

Processor

Processor frequency:	0.52 GHz
Processor family:	Intel XScale
Processor model:	PXA270

Memory

Internal memory:	0.128 GB
------------------	----------

Multimedia

Built-in speaker(s):	Y
Card reader integrated:	Y
Compatible memory cards:	SD

Networking

Ethernet LAN:	Y
Ethernet LAN data rates:	10,100 Mbit/s
Wi-Fi:	Y
Wi-Fi standards:	802.11b,802.11g

Ports & interfaces

Ethernet LAN (RJ-45) ports:	1
USB 2.0 ports quantity:	2
Serial ports quantity:	2

Software

Operating system installed:	Windows Mobile 5
-----------------------------	------------------

Operational conditions

Operating relative humidity (H-H):	5 - 95 %
Operating temperature (T-T):	-30 - 50 °C
Storage temperature (T-T):	-30 - 70 °C

Certificates

Certification:	FCC Part 15.247, Industry Canada RSS 210, EN 300 328-2, Telecom. Num. 547, cULus Listed, OSHA 29 CFR 1910.178 / ASME B56.11.6 Compliant, GS, CCC, GOST, NOM, eK, HKSI, SABS, SPRING, prEN ISO 13564, FCC Part 15B – Class B, ICES-003 Class B, EN 55022 Class B, EN 55024, EN 301 489-17, AS/ZNS 3548, GB9254-1998
----------------	--

Weight & dimensions

Width:	189.2 mm
Depth:	54.6 mm
Height:	176.5 mm
Weight:	1470 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.