

## Intermec CN70e handheld mobile computer (CN70EQ2KCU3W2100)

CN70E, Num+QW, 3.5" VGA Touch, 480x640, TI OMAP3, 512MB &#8203;&#8203;RAM, 1GB Flash, MicroSD, USB 2.0, EA30 1D/2D, 5MP LED Cam, UMTS, 802.11 a/b/g/n, Bluetooth 2.1+EDR, Li-Ion/4000 mAh, 491g, SmartSystems, Windows Mobile 6.5, Black/Grey



### Price details:

Price excl. VAT: 1,671.41 €

Eco fees: 0.00 €

VAT 21 %: 351.00 €

### Product details:

Product code: CN70EQ2KCU3W2100

EAN:

Manufacturer: Intermec

**2,022.41 €**

\* VAT included

PDF generated on: 11 December, 2017



### Ultra-Rugged Mobile Computers

The Intermec CN70e Ultra-Rugged Mobile Computer ideal for field-mobility applications that demand a compact form factor with no compromise on ruggedness. Next-generation architecture, combined with market-leading wireless communications and data capture capabilities, delivers optimal worker productivity.

- Power-packed mobile computing in terms of size, weight and ruggedness;
- Exceptional battery life for long device run time without extra size and weight;
- Advanced bar code imaging technology with motion tolerance for snappy scanning and white illumination with laser aiming for high read rates;
- Brilliant display with extended life touch panel;
- On-board diagnostics provides device health visibility and reduces downtime;
- Full compatibility with printers, application software, communications, and a complete set of peripherals and accessories enabling a comprehensive enterprise business solution.

### Main specifications:

#### Display

|                            |                  |
|----------------------------|------------------|
| Display diagonal:          | 3.5 "            |
| Display resolution:        | 480 x 640 pixels |
| Touchscreen:               | Y                |
| Display number of colours: | 65536 colours    |

#### Memory

|                       |         |
|-----------------------|---------|
| Internal memory:      | 512 MB  |
| Internal memory type: | RAM     |
| Flash memory:         | 1024 MB |
| ROM capacity:         | 1024 MB |

#### Processor

|                         |                   |
|-------------------------|-------------------|
| Processor family:       | Instruments OMAP  |
| Processor manufacturer: | Texas Instruments |

#### GPS Performance

|                  |   |
|------------------|---|
| GPS (satellite): | N |
|------------------|---|

#### Software

|                             |                    |
|-----------------------------|--------------------|
| Operating system installed: | Windows Mobile 6.5 |
|-----------------------------|--------------------|

|                                |   |
|--------------------------------|---|
| Bundled software:              | SmartSystems  |
| <b>Networking</b>              |   |
| GSM bands supported:           | 850,900,1800,1900 MHz   |
| WCDMA bands supported:         | 800,850,900,1900,2100 MHz   |
| <b>Wireless LAN features</b>   |   |
| Wi-Fi:                         | Y   |
| Wireless technology:           | Wi-Fi   |
| Wi-Fi standards:               | 802.11a,802.11b,802.11g,802.11n   |
| Security algorithms:           | 128-bit WEP,64-bit WEP,802.1x RADIUS,TKIP,WPA,WPA-AES,WPA2  |
| <b>Data transmission</b>       |   |
| Bluetooth:                     | Y   |
| Data network:                  | 3G,GPRS,GSM,HSUPA,WCDMA   |
| Bluetooth version:             | 2.1+EDR   |
| <b>Camera</b>                  |   |
| Built-in camera:               | Y   |
| Megapixel:                     | 5 MP  |
| Second camera:                 | N   |
| Auto focus:                    | Y   |
| Built-in flash:                | Y   |
| <b>Audio</b>                   |   |
| Built-in microphone:           | Y   |
| Speakers:                      | Y   |
| Voice recording:               | Y   |
| Speech recognition:            | Y   |
| <b>Ports &amp; interfaces</b>  |   |
| USB 2.0 ports quantity:        | 1   |
| <b>Operational conditions</b>  |   |
| Storage temperature (T-T):     | -30 - 70 °C   |
| Operating temperature (T-T):   | -20 - 60 °C   |
| Relative humidity:             | 0 - 95 %  |
| <b>Power</b>                   |   |
| Battery capacity:              | 4000 mAh  |
| Battery technology:            | Lithium-Ion (Li-Ion)  |
| <b>System requirements</b>     |   |
| Compatibility:                 | CCXv4   |
| Compatible operating systems:  | Windows Mobile 6.5  |
| <b>Weight &amp; dimensions</b> |   |
| Weight:                        | 491 g   |
| Width:                         | 80 mm   |
| Depth:                         | 195 mm  |
| Height:                        | 34 mm   |
| Dimensions (WxDxH):            | 80 x 195 x 34 mm  |
| <b>Technical details</b>       |   |
| Phone function:                | N   |
| RFID reader:                   | N   |
| Certification:                 | cULus, DEMKO, BSMI, EMV, ICES, EN, GOS-R, FCC, A-tick, C-tick, NCC, OFTA, IDA, ICASA, POSTEL, NTC, ETA, SIRIM, ANATEL, WEEE, RoHS |
| Keyboard layout:               | QWERTY  |
| LED indicators:                | Y   |
| Barcode reader:                | Y   |

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.