

# Intermec PC43d label printer (PC43DA00100202)

PC43DA00100202 LCD, Latin Font, RTC, 203DPI, EU PC



## Price details:

Price excl. VAT: 275.07 €

Eco fees: 0.04 €

VAT 21 %: 57.77 €

## Product details:

Product code: PC43DA00100202

EAN: 5711045623820

Manufacturer: Intermec



**332.88 €**

\* VAT included

PDF generated on: 21 February, 2019

Featuring innovative designs guided by customer input, the PC series are optimized for healthcare, retail and hospitality markets - as well as light-duty manufacturing, warehousing and general office duties.

Designed for user-friendliness and flexibility, compact PC series desktop printers provide an intuitive label printing solution. Available in two-inch wide direct thermal (PC23d), four-inch wide direct thermal (PC43d), or four-inch wide thermal transfer (PC43t) models, PC series printers are perfect for space-constrained settings. Their low cost and fast operation make them the smart choice for light duty labeling applications where users need reliable, easy-to-use printers.

PC series printers were designed for quick set-up and trouble-free use. With a variety of placement options including wall-mounted and battery-powered, these printers adapt to their environment and fit right in. Common printer tasks are simple and training needs are reduced, because PC series printers come with either a universal icon interface or color LCD in ten languages. It's even possible to configure and update your printer on the spot, using a USB thumbdrive - no computer necessary.

- Ten-language LCD or intuitive icon graphical user interface. Simple to use and maintain, with easy one-handed media reloading
- Comprehensive printer command language support, including ZSim2, makes upgrading easy
- Flexible, with user-installable connectivity upgrades and accessories
- This Smart Printer runs apps right inside the printer; you can add keyboards, scanners or other USB peripherals for increased efficiency

## Main specifications:

### Printing

Print technology:	Direct thermal
Maximum resolution:	203 x 203 DPI
Print speed:	203.2 mm/sec
Standard printer languages:	IPL, XML, ZPL II

### Display

Display:	LCD
Display resolution:	314 x 234 pixels
Backlight display:	Y
Backlight colour:	Blue

### Ports & interfaces

USB 2.0 ports quantity:	2
-------------------------	---

### Memory

Internal memory:	128 MB
Flash memory:	128 MB

### Paper handling

Maximum label width:	118 mm
Maximum label length:	1.727 m
Maximum roll diameter:	127 mm

#### Performance

Built-in barcodes:	1D,2D,Code 49,EAN13,MaxiCode,PDF417,POSTNET
Ribbon width:	110 mm

#### Design

Colour of product:	Grey
LED indicators:	Y

#### Power

Energy Star certified:	Y
AC input voltage:	100 - 240 V
AC input frequency:	50/60 Hz
Input current:	1.5 A
AC adapter output voltage:	24 V
AC adapter output current:	2.5 A
Power consumption:	1500 mA

#### Weight & dimensions

Width:	180 mm
Depth:	215 mm

#### Operational conditions

Operating relative humidity (H-H):	10 - 80 %
Operating temperature (T-T):	5 - 40 °C