

# Intermec CK3R handheld mobile computer (CK3RAB4S000W4100)

8.89 cm (3.5 ") 240 x 320, Numerical, EA31, 256MB RAM, 512MB ROM, Texas Instruments 1GHz, USB 2.0, 2000 mAh, WLAN 802.11 b/g/n, Bluetooth 2.1+EDR, 401g, WM LP STD. SW IN



## Price details:

Price excl. VAT: 1,006.22 €

Eco fees: 0.04 €

VAT 21 %: 211.31 €

## Product details:

Product code: CK3RAB4S000W4100

EAN: 5712505723241

Manufacturer: Intermec

**1,217.57 €**

\* VAT included

PDF generated on: 23 October, 2017



- Rugged - Withstands multiple 1.2m (4ft) drops to concrete across all operating temperature ranges and an IP54 seal rating against rain and dust
- Scanning - Integrated high motion tolerance 2D area imager supports high-performance, omni-directional scanning
- Radio - Supports industry standard 802.11 b/g/n and Bluetooth radio for adaptable communications
- Battery - Industry-leading battery performance will last a full shift and beyond
- Processor - Equipped with a power-efficient 1GHz multi-engine Texas Instruments processor, 256MB RAM and 512MB Flash

Optimize your operations into an efficient, automated, and high-performing work environment with the CK3R, the mobile computer you can count on to keep your workers running productively at full speed to deliver enhanced workflow performance.

Thanks to a state-of-the-art power efficient design, the CK3R delivers full-shift battery life - even when running scan- and network-intensive applications and with a purpose-built, slim and lightweight-design, the CK3R is comfortable and easy to use. And with CloneNGo - our breakthrough device provisioning technology - you can greatly simplify and expedite configuration and deployment of your CK3R mobile computers from a single master unit without requiring sophisticated IT support.

Scanning operations are quick and accurate, with integrated high performance area imaging technology pioneered by Intermec. Support for omni-directional scanning and high motion tolerance means your 1D and 2D bar codes can scan correctly the first time, at most angles, even if the code itself is not perfect.

The CK3R is also designed to stand up to the rigors of everyday use with a rugged, laser-etched keypad, a 1.2 meter (4 ft) drop rating to concrete (across all operating temperatures) and an IP54 seal rating against rain, moisture and dust.

Running the latest Microsoft® Windows Embedded Handheld operating system, the CK3R supports the wide range of enterprise software applications. And the optional Intermec Client Pack, which includes full Terminal Emulation and a lock-down web browser supporting emerging industry standards like HTML5, provides a consistent user interface and common menu structure to ensure that workflow is directed and web access is limited.

Achieving workflow automation has never been easier. The CK3R can be combined with Intermec printers, scanners and service for a proven enterprise business solution to automate your data collection tasks without introducing IT complexity. Put the CK3R to work and unlock the full potential of your operations.

## Main specifications:

### Display

Display diagonal:	3.5 "
Display resolution:	240 x 320 pixels
Touchscreen:	Y
Display number of colours:	65536 colours
<b>Memory</b>	
Internal memory:	256 MB
Internal memory type:	RAM
Compatible memory cards:	microSD (TransFlash)
ROM capacity:	512 MB
Maximum memory card size:	32 GB
<b>Processor</b>	
Processor frequency:	1000 MHz
Processor family:	Instruments OMAP
Processor manufacturer:	Texas Instruments
<b>GPS Performance</b>	
GPS (satellite):	N
<b>Software</b>	
Bundled software:	SmartSystems
<b>Wireless LAN features</b>	
Wi-Fi:	Y
Wi-Fi standards:	802.11b,802.11g,802.11n
Security algorithms:	128-bit WEP,64-bit WEP,WPA,WPA-AES,WPA-TKIP,WPA2
<b>Data transmission</b>	
Bluetooth:	Y
Bluetooth version:	2.1+EDR
<b>Camera</b>	
Built-in camera:	N
<b>Audio</b>	
Built-in microphone:	Y
Speakers:	Y
Voice recording:	Y
Speech recognition:	Y
<b>Ports &amp; interfaces</b>	
USB 2.0 ports quantity:	1
<b>Operational conditions</b>	
Storage temperature (T-T):	-20 - 70 °C
Operating temperature (T-T):	-10 - 50 °C
Operating temperature (T-T):	14 - 122 °F
Relative humidity:	0 - 95 %
<b>Power</b>	
Battery capacity:	2000 mAh
Battery technology:	Lithium-Ion (Li-Ion)
<b>System requirements</b>	
Compatibility:	CCXv4
<b>Weight &amp; dimensions</b>	
Weight:	401 g
Width:	83 mm
Depth:	28 mm
Height:	216 mm
<b>Technical details</b>	
Phone function:	N
RFID reader:	N
Certification:	cULus Listed, DEMKO, BSMI, Class B &#8211; FCC/ICES/EN, GOST-R, CE, CCC, FCC, Industry Canada, C-tick (AU/NZ), NCC, OFCA, IDA, ICASA, POSTEL, NTC, KC (Korea), ETA, ANATEL
Keyboard layout:	Numeric
LED indicators:	Y
Barcode reader:	Y

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.