

## Intermec CK3X handheld mobile computer (CK3XAB4M000W4100)

8.89 cm (3.5 ") 240 x 320, Numerical, EX25, 256MB RAM, 1GB Flash, Texas Instruments 1GHz, USB 2.0, 5100 mAh, WLAN 802.11 a/b/g/n, Bluetooth 2.1+EDR, 499g, WM LP Std. SW



### Price details:

Price excl. VAT: 1,400.71 €

Eco fees: 0.04 €

VAT 21 %: 294.16 €

### Product details:

Product code: CK3XAB4M000W4100

EAN: 5712505723142

Manufacturer: Intermec

**1,694.91 €**

\* VAT included

PDF generated on: 18 October, 2017



- Rugged - Withstands multiple 1.5m (5ft) drops to concrete across all operating temperature ranges and an IP54 seal rating against rain and dust
- Scanning - Choice of integrated high motion tolerance 2D area imager or 2D near/far area imager supports high-performance, omni-directional scanning
- Radio - Supports industry standard 802.11 a/b/g/n and Bluetooth radio for adaptable communications
- Battery - Industry-leading battery performance will last a full shift and beyond
- Processor - Equipped with a powerefficient 1GHz multi-engine Texas Instruments processor, 256MB RAM and 1GB Flash
- Voice - Designed to support Vocollect Voice to combine voice-directed workflow with traditional barcode data collection
- RFID - Optional field-installable RFID reader to adapt with your changing data collection needs

With the pace and competitiveness of business today, it's no secret that customers expect accurate orders to be delivered on-time and damage-free, every time. Putting cost-effective processes and technologies in place to improve workforce and workflow performance is vital to the success of your operations.

The CK3X fits your timetable for achieving such results with a pedigree of proven success, easy deployment and fast return on investment. Extending the popular ergonomic design of the CK3 model, the CK3X takes the best and makes it even better, giving you the power to put accuracy and productivity in the hands of your workers.

The CK3X comes with a choice of integrated area imagers for standard range or near/far range scanning. These imagers provide unsurpassed scanning performance on 1D and 2D bar codes and are particularly well-suited for reading poor quality and damaged codes. Support for omni-directional scanning and very high motion tolerance allows workers to capture an accurate scan and quickly move to the next task.

Featuring a highly adaptable design, the CK3X is supported by an 802.11 a/b/g/n and Bluetooth® radio, as well as an optional RFID reader accessory. Designed to support Vocollect Voice, you can quickly combine the proven results associated with voice-directed workflow or combine it with traditional bar code data collection all in the same device.

Avoid downtime with a device that is truly rugged. The CK3X can withstand multiple 1.5 meter (5 ft) drops to concrete (across all operating temperatures) and delivers industry-leading battery life performance that will last through a full shift and beyond - no more interruption to replace or recharge batteries. Best of all, this comes without the bulk and size of traditional rugged devices in the same class.

Transitioning from other computers to the CK3X is easy with device configuration tools like CloneNGo our breakthrough device provisioning that makes it easy to "clone" device settings from a single master unit to an unlimited number of devices. The latest Microsoft® Windows Embedded Handheld operating system and broad compliance for the latest industry standards such as HTML5 means the CK3X is compatible with the widest range of software applications - from warehouse management systems to other mission-critical tools developed by our PartnerNet Independent Service Provider (ISV) community.

Legacy applications are backwards compatible, and the optional Intermec Client Pack includes Terminal Emulation and a lock-down browser which simplify migrations. Plus the CK3X is compatible with existing CK3 accessories so you can upgrade to the latest technology, without additional investment in chargers, docking stations, scan handles and more.

Take your business performance to the next level with CK3X. As part of Intermec's proven enterprise business solutions, the CK3X extends your data collection options while reducing IT burden - giving you a true competitive edge.

---

#### Main specifications:

##### Display

|                            |                  |
|----------------------------|------------------|
| Display diagonal:          | 3.5 "            |
| Display resolution:        | 240 x 320 pixels |
| Touchscreen:               | Y                |
| Display number of colours: | 65536 colours    |

##### Memory

|                           |                      |
|---------------------------|----------------------|
| Internal memory:          | 256 MB               |
| Internal memory type:     | RAM                  |
| Compatible memory cards:  | microSD (TransFlash) |
| Flash memory:             | 1024 MB              |
| ROM capacity:             | 1024 MB              |
| Maximum memory card size: | 32 GB                |

##### Processor

|                         |                   |
|-------------------------|-------------------|
| Processor frequency:    | 1000 MHz          |
| Processor family:       | Instruments OMAP  |
| Processor manufacturer: | Texas Instruments |

##### GPS Performance

|                  |   |
|------------------|---|
| GPS (satellite): | N |
|------------------|---|

##### Wireless LAN features

|                      |  |
|----------------------|--|
| Wi-Fi:               | Y  |
| Wi-Fi standards:     | 802.11a,802.11b,802.11g,802.11n                  |
| Security algorithms: | 128-bit WEP,64-bit WEP,WPA,WPA-AES,WPA-TKIP,WPA2 |

##### Data transmission

|                    |         |
|--------------------|---------|
| Bluetooth:         | Y       |
| Bluetooth version: | 2.1+EDR |

##### Camera

|                  |   |
|------------------|---|
| Built-in camera: | N |
|------------------|---|

##### Audio

|                      |   |
|----------------------|---|
| Built-in microphone: | Y |
| Speakers:            | Y |
| Voice recording:     | Y |
| Speech recognition:  | Y |

##### Ports & interfaces

|                         |   |
|-------------------------|---|
| USB 2.0 ports quantity: | 1 |
|-------------------------|---|

##### Operational conditions

|                              |             |
|------------------------------|-------------|
| Storage temperature (T-T):   | -20 - 70 °C |
| Operating temperature (T-T): | -10 - 50 °C |
| Operating temperature (T-T): | 14 - 122 °F |
| Relative humidity:           | 0 - 95 %    |

##### Power

|                     |                      |
|---------------------|----------------------|
| Battery capacity:   | 5100 mAh             |
| Battery technology: | Lithium-Ion (Li-Ion) |

##### System requirements

|                |       |
|----------------|-------|
| Compatibility: | CCXv4 |
|----------------|-------|

##### Weight & dimensions

|         |        |
|---------|--------|
| Weight: | 499 g  |
| Width:  | 83 mm  |
| Depth:  | 61 mm  |
| Height: | 216 mm |

##### Technical details

|                  |  |
|------------------|--|
| Phone function:  | N  |
| RFID reader:     | N  |
| Certification:   | cULus Listed, DEMKO, BSMI, Class B &#8211; FCC/ICES/EN, GOST-R, CE, CCC, FCC, Industry Canada, C-tick (AU/NZ), NCC, OFCA, IDA, ICASA, POSTEL, NTC, KC (Korea), ETA, ANATEL, WEEE, RoHS |
| Keyboard layout: | Numeric  |
| LED indicators:  | Y  |
| Barcode reader:  | Y  |

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.