

# Intermec PM43CA label printer (PM43CA0130040402)

PM43CA,OB,ROW,ETH,LG+F,REW+LTS,HGR,TT406



## Price details:

Price excl. VAT: 1,681.56 €

Eco fees: 0.04 €

VAT 21 %: 353.14 €

## Product details:

Product code: PM43CA0130040402

EAN:

Manufacturer: Intermec

PDF generated on: 21 May, 2018



**2,034.74 €**

\* VAT included

## Product Overview

PM43/PM43c mid-range industrial printers are ideal for a wide range of applications within the distribution center / warehouse and manufacturing environments.

Ready - Fastest to Deploy. Seamlessly Fits Any Environment.

- Large, color, multilingual, tamper-proof touch screen, or icon user interface
- "No-touch" configuration capabilities
- The only CCX- and WiFi-certified fixed printer with standard IPv6 implementation

Reliable - Maximizes Uptime. Built from 40 Years of Printing Innovation. Third-Generation Platform.

- Precision Print, for consistent bar-code printing with pinpoint accuracy
- Multilingual webpage loaded on every printer ensures easy device monitoring
- Strong metal structure with metal door that can be locked for media protection

Perform - Increase Productivity and Process Efficiencies. Simple to Use.

- Fastest throughput in its class
- Powerful programmable capability, with ability to directly connect peripherals
- Most connectivity options of any printer on the market

## Main specifications:

### Printing

Print technology:	Direct thermal / thermal transfer
Maximum resolution:	203 x 203 DPI
Print speed:	300 mm/sec

### Display

Display:	LCD
Backlight display:	Y
Backlight colour:	Blue

### Ports & interfaces

Ethernet LAN:	Y
Wi-Fi:	Y
Connectivity technology:	Wired & Wireless
USB 2.0 ports quantity:	1
RS-232 ports:	1

### Memory

Internal memory:	128 MB
Flash memory:	128 MB
<b>Paper handling</b>	
Maximum label length:	4.8 m
<b>Performance</b>	
Built-in barcodes:	1D,2D
<b>Design</b>	
Colour of product:	Grey
Certification:	RoHS, CE, FCC A, UL/cUL, C-Tick, D Mark, CCC
<b>Weight &amp; dimensions</b>	
Width:	284 mm
Depth:	431.84 mm
Weight:	12500 g
<b>Operational conditions</b>	
Operating relative humidity (H-H):	10 - 80 %
Operating temperature (T-T):	5 - 40 °C
Storage temperature (T-T):	-20 - 70 °C

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.