

Intermec SG20B (SG20B1D-002)

1D, Linear, IP30, 61x200x65mm, 175g, Black



Price details:

Price excl. VAT: 212.92 €

Eco fees: 0.04 €

VAT 21 %: 44.72 €

Product details:

Product code: SG20B1D-002

EAN:

Manufacturer: Intermec

257.68 €

* VAT included

PDF generated on: 19 November, 2017



Overview

Speed up your customers' checkout experience with an SG20 handheld scanner - ergonomically designed for countertop scanning applications in retail, office, library, and light manufacturing. Also available in a specialized healthcare version. (Wired or wireless)

Choice

The SG20 series is available with 1D or 2D scan engines, laser- or LED-based aimers, wired or wireless connectivity, and standard or healthcare configurations.

Snappy

Available with the EA30 or EA31 imagers, providing high motion tolerance for responsive, dependable scanning.

Comfortable

Unique, ergonomic styling maximizes comfort and saves countertop space

Accessorize

Choose from a wide range of multi-purpose accessories that increase scanner flexibility.

Visually Stunning

A large LED lightpipe indicator provides effective visual operational feedback.

Easy to Connect

Integrates seamlessly with point of sale systems, iOS and Android devices, personal computers, and common software solutions.

Healthcare-Ready Version

Available in a specialized healthcare version. Its disinfectant-ready housing and LED-based aimer are ideal for patient-facing applications.

Main specifications:

Scanning

Scanner type:

1D

Sensor type:

Linear

Linear (1D) barcodes supported:

Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar Omnidirectional, GS1-128 (UCC/EAN-128), Interleaved 2 of 5, Plessey, Telepen

Ports & interfaces

Connectivity technology:

Wireless

Interface:

USB + RS-232 + Bluetooth

Wireless range:

10 m

Bluetooth version:

2.1+EDR

Design

Colour of product:

Black

Type:

Handheld bar code reader

International Protection (IP) code:

IP30

RoHS compliance:

Y

Certification:

FCC Part 15 Class B, ICES-003 Class B, EN 55022: CISPR 22 Class B, WEEE, REACH, UL, CE, IDA, C-TICK, ANATEL,

Performance

Light levels (direct sunlight):

0 - 100000 lx

Power

Power source type:

Battery

Battery technology:

Lithium-Ion (Li-Ion)

Battery capacity:

1567 mAh

Power consumption:

120 mA

Operational conditions

Operating temperature (T-T):

0 - 50 °C

Storage temperature (T-T):

-20 - 60 °C

Operating relative humidity (H-H):

5 - 95 %

Weight & dimensions

Weight:

175 g

Width:

61 mm

Depth:

200 mm

Height:

65 mm

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.