

Intermec SR61 (SR61BHP-CB-001)

SR61BHP-CB-001 HP SCANNER, BATTERY, CHARGE BASE, PS (SR61BHP Scanner kit, includes charge base and power supply (order AC line cord separately))



Price details:

Price excl. VAT: 593.85 €

Eco fees: 0.30 €

VAT 21 %: 124.77 €

Product details:

Product code: SR61BHP-CB-001

EAN: 0768497748309

Manufacturer: Intermec

718.92 €

* VAT included

PDF generated on: 24 May, 2018



Dependable linear scanning in a dependable package. Tested to exceed industrial and military specifications, you can rely on SR61 in the most demanding environments. Let downtime be a thing of the past

Specifications

- Rugged: designed to withstand 26 drops to concrete or steel from 6.5 feet, hot and cold temperature extremes, constant forklift vibration and windblown dust and rain.
- Easy to use: bright LED aimer makes targeting bar codes fast and efficient.
- Ergonomic: comfort grip and trigger location improve operator efficiency
- Fast: full speed USB 2.0 wired or Bluetooth® wireless interface to quickly transfer bar code data images to host system.

Main specifications:

Scanning

Scanner type:	1D/2D
Sensor type:	Linear
Linear (1D) barcodes supported:	Code 128, Code 39, Code 93, GS1 DataBar Expanded, GS1 DataBar Omnidirectional, PDF417
2D (matrix & stacked) barcodes supported:	GS1 DataBar Expanded Stacked, GS1 DataBar Stacked Omnidirectional, MicroPDF417, PDF417, TLC-39
Working distance:	700 mm

Ports & interfaces

Connectivity technology:	Wired & Wireless
Interface:	USB + RS-232 + Bluetooth
Wireless range:	30 m
USB version:	2.0
Bluetooth version:	2.1+EDR

Design

Colour of product:	Black, Blue
Type:	Handheld bar code reader
International Protection (IP) code:	IP54

Performance

Light levels (direct sunlight):	0 - 100000 lx
---------------------------------	---------------

Power

Power source type:	Battery
Input voltage:	5 V
Input frequency:	2.4 Hz

Operational conditions

Operating temperature (T-T):	-30 - 50 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	5 - 95 %

Weight & dimensions

Weight:	425 g
Width:	70 mm
Depth:	178 mm
Height:	114 mm

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.