

Intermec SG20B 2D Imager (SG20BHP-002)

SG20BHP-002 SG20 2D EA30, BIK, BT, USB/KBW/232 I/F (2D cordless High Performance EA30 imager, scanner only, cable & base station ordered separately)



Price details:

Price excl. VAT: 358.55 €

Eco fees: 0.00 €

VAT 21 %: 75.30 €

Product details:

Product code: SG20BHP-002

EAN: 0735548764434

Manufacturer: Intermec

PDF generated on: 20 February, 2019



433.85 €

* VAT included

Speed up the customer checkout experience with the SG20 handheld scanner, available with the industry's fastest 2D bar code imaging technology for quick, flawless scans - every time. Ergonomically designed for the needs of countertop scanning applications in retail, office, library, and light manufacturing.

- Features the industry's fastest 2D imaging technology for highly responsive, dependable scanning
- Unique, ergonomic styling maximizes comfort and saves countertop space
- Large LED indicator provides effective visual operational feedback
- Choice of options matched to your scanning needs: 1D or 2D scan engines, laser- or LED-based aimer, tethered or Bluetooth wireless
- Wide range of multi-purpose accessories increase scanner flexibility
- Integrates seamlessly with point of sale systems, iOS® and Android® devices, personal computers, and common software solutions

Main specifications:

Scanning

Scanner type:	2D
Sensor type:	LED
2D (matrix & stacked) barcodes supported:	Aztec Code,Codablock,GS1 DataBar Expanded Stacked,GS1 DataBar Stacked Omnidirectional,MaxiCode,Micro QR Code,MicroPDF417,PDF417,QR Code,TLC-39

Ports & interfaces

Connectivity technology:	Wired & Wireless
Wireless range:	10 m
Bluetooth version:	2.1+EDR

Design

Colour of product:	Black,Grey
Type:	Handheld bar code reader
International Protection (IP) code:	IP30
LED indicators:	Y
RoHS compliance:	Y

Power

Power source type:	Battery
Battery technology:	Lithium-Ion (Li-Ion)
Number of batteries supported:	1
Battery capacity:	1567 mAh
Charging time:	3 h
Input voltage:	5 V

Power consumption: 330 mA

Operational conditions

Operating temperature (T-T): 0 - 50 °C

Storage temperature (T-T): -20 - 60 °C

Operating relative humidity (H-H): 5 - 95 %

Weight & dimensions

Weight: 175 g

Width: 61 mm

Depth: 200 mm

Height: 65 mm