

Intermec SR61B (SR61BL-CB-001)

Laser 1D, EL20, Bluetooth 2.1+EDR, Li-Ion battery, IP54, 425 g, incl. charge base



Price details:

Price excl. VAT: 548.98 €

Eco fees: 0.00 €

VAT 21 %: 115.29 €

Product details:

Product code: SR61BL-CB-001

EAN:

Manufacturer: Intermec

664.27 €

* VAT included

PDF generated on: 22 March, 2018



The Intermec SR61 handheld scanner family is built for rugged applications in warehouse, distribution and industrial manufacturing, and also supports proof of delivery and point of service applications. With a high impact, virtually impenetrable housing and a solid state design, the SR61 exceeds industrial and military standards and can be counted on to perform well in harsh environments where dust, moisture or extreme temperatures are constants and operational uptime is critical.

Choose between a linear area imager or laser scan engine, both of which allow for fast scanning of virtually all 1D bar code symbologies. With both scan engines rated at greater than 200 scans per second, the SR61 linear scanner delivers the rapid performance you need for point-of-service applications. And advanced capabilities-such as support for data manipulation (data parsing)-increase scanner flexibility and helps ensure seamless integration with your existing application infrastructure.

With multiple scanning configurations, including tethered or wireless connectivity, the SR61 linear scanner can be tailored to your environment-whether this includes reading specific bar code symbologies or decoding poor quality or damaged symbols. Support for both legacy 1D bar code symbologies, as well as today's most commonly used 1D symbologies such as GS1, ensures reliable performance in your tough applications.

- Rugged - designed to withstand 26 drops to concrete or steel from 6.5 feet, hot and cold temperature extremes, constant forklift vibration and windblown dust and rain
- Reliable performance - easily scan today's common 1D symbologies, such as GS1, and can even decode poor quality or damaged symbols
- Easy to use - bright LED aimer makes targeting bar codes fast and efficient
- Ergonomic - comfort grip and trigger location improve operator efficiency
- Fast - full speed USB 2.0 wired or Bluetooth® wireless interface for quick transfer to host system
- Proven - part of a complete line-up of proven SR61 scanners

Main specifications:

Scanning

Scanner type:	1D
Sensor type:	Laser
Linear (1D) barcodes supported:	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, GS1 DataBar Expanded, GS1 DataBar Omnidirectional, GS1-128 (UCC/EAN-128), Interleaved 2 of 5, MSI, PDF417, Plessey, Telepen, U.P.C.

Ports & interfaces

Connectivity technology:	Wireless
Interface:	Bluetooth
Wireless range:	100 m
Bluetooth version:	2.1+EDR
Operating frequency:	2400 MHz

Design

Colour of product:	Black,Blue
Type:	Handheld bar code reader
International Protection (IP) code:	IP54
RoHS compliance:	Y
Certification:	ANATEL, CE, COFETEL, cULus, C-TICK, KCC, SRRS, FCC.
Performance	
Built-in display:	N
Light levels (direct sunlight):	0 - 100000 lx
Power	
Power source type:	Battery
Battery technology:	Lithium-Ion (Li-Ion)
Number of batteries supported:	1
Battery life:	10 h
Charging time:	2.5 h
Operational conditions	
Operating temperature (T-T):	-20 - 50 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	0 - 95 %
Weight & dimensions	
Weight:	425 g
Width:	70 mm
Depth:	178 mm
Height:	114 mm
Packaging content	
Charging base:	Y

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.