

Intermec CN70e handheld mobile computer (CN70EN7KD00W1100)

Texas Instruments OMAP 1 GHz, 8.89 cm (3.5 ") LED (480 x 640) Touch Screen, WLAN 802.11 a/b/g/n, GPS, Numeric, EA30, Camera, WEH - P, WWE, SS, USB, Li-Ion (3.7 V, 1000 mAh), Microsoft Windows Embedded Handheld 6.5



Price details:

Price excl. VAT: 1,866.97 €

Eco fees: 0.00 €

VAT 21 %: 392.06 €

Product details:

Product code: CN70EN7KD00W1100

EAN:

Manufacturer: Intermec

2,259.03 €

* VAT included

PDF generated on: 23 February, 2018



Ultra-Rugged Mobile Computer

The Intermec CN70 and CN70e Ultra-Rugged Mobile Computers are ideal for field-mobility applications that demand a compact form factor with no compromise on ruggedness. Next-generation architecture, combined with market-leading wireless communications and data capture capabilities, delivers optimal worker productivity.

Features

- Power-packed mobile computing in terms of size, weight and ruggedness
- Superior computing performance and application response time
- Flexible radio technology provides optimal network coverage and a superior solution for implementing least cost routing strategies
- Exceptional battery life for long device run time without extra size and weight
- Advanced bar code imaging technology with motion tolerance for snappy scanning and white illumination with laser aiming for high read rates
- Brilliant display with extended life touch panel
- On-board diagnostics provides device health visibility and reduces downtime
- Full compatibility with printers, application software, communications, and a complete set of peripherals and accessories enabling a comprehensive enterprise business solution
- Non-Incendive option for hazardous locations CN70 and CN70e

Main specifications:

Display

| | |
|----------------------------|------------------|
| Display diagonal: | 3.5 " |
| Display resolution: | 480 x 640 pixels |
| Touchscreen: | Y |
| Display: | LED |
| Display number of colours: | 65536 colours |

Memory

| | |
|---------------------------|--------------------------------|
| Internal memory: | 512 MB |
| Internal memory type: | RAM |
| Compatible memory cards: | MicroSD (TransFlash),MicroSDHC |
| Flash memory: | 1024 MB |
| Maximum memory card size: | 32 GB |

Processor

| | |
|---|--|
| Processor frequency: | 1000 MHz |
| Processor manufacturer: | Texas Instruments |
| Built-in processor: | OMAP |
| GPS Performance | |
| GPS (satellite): | Y |
| Channels quantity: | 12 channels |
| Software | |
| Operating system installed: | Windows Embedded Handheld 6.5 |
| Wireless LAN features | |
| Wi-Fi: | Y |
| Wi-Fi standards: | 802.11a,802.11b,802.11g,802.11n |
| Security algorithms: | 128-bit WEP,64-bit WEP,802.1x RADIUS,AES,TKIP,WPA,WPA2 |
| Data transmission | |
| Bluetooth: | Y |
| Bluetooth version: | 2.1+EDR |
| Camera | |
| Built-in camera: | Y |
| Megapixel: | 5 MP |
| Second camera: | N |
| Auto focus: | Y |
| Built-in flash: | Y |
| Audio | |
| Built-in microphone: | Y |
| Voice recording: | Y |
| Ports & interfaces | |
| USB 2.0 ports quantity: | 1 |
| Operational conditions | |
| Storage temperature (T-T): | -30 - 70 °C |
| Operating relative humidity (H-H): | 0 - 95 % |
| Operating temperature (T-T): | -20 - 60 °C |
| Power | |
| Battery capacity: | 4000 mAh |
| Battery technology: | Lithium-Ion (Li-Ion) |
| Weight & dimensions | |
| Weight: | 491 g |
| Width: | 80 mm |
| Depth: | 34 mm |
| Height: | 169 mm |
| Technical details | |
| Colour of product: | Black |
| RFID reader: | N |
| Certification: | cULus, DEMKO, BSMFCC/ICES/EN, GOST-R |
| International Protection (IP) code: | IP67 |
| Handle(s): | N |
| Linear (1D) barcodes supported: | U.P.C. |
| 2D (matrix & stacked) barcodes supported: | Data Matrix |
| Barcode reader: | Y |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.