

Jabra Evolve 75e mobile headset (7099-823-309)

Evolve 75e, IP54, 150Hz - 6.8kHz, Bluetooth 4.2



Price details:

Price excl. VAT: 156.67 €

Eco fees: 0.04 €

VAT 21 %: 32.91 €

Product details:

Product code: 7099-823-309

EAN: 5706991020816

Manufacturer: Jabra

PDF generated on: 11 December, 2018



189.62 €

* VAT included

Professional sound. The way you want to wear it.

The three-microphone technology creates a unique talk-zone, making sure you are heard, while other nearby voices are filtered out. With an around-the-neck, wireless earbud design.

Featuring battery technology similar to that found in your smartphone. It fully charges in just two hours, and that charge provides up to 14 hours of battery life

Calls and music that lasts as long as you need it. All day long.

Powerful at work. Fully concentrate, whatever the noise around you.

Focus with Active Noise Cancellation, and an integrated busylight lets colleagues know you are not to be disturbed

Smart controls for work and play

Five buttons for quick control of calls and music, including a smart button for one-touch access to Siri® and Google Now, and a vibrating neckband to give silent notifications.

Multiple fitting options.

Personalized fit for an improved experience. Multiple fitting options for gels and EarWings give amazing comfort throughout the day

Main specifications:

Design

Headset type:	Binaural
Wearing style:	Neck-band
Colour of product:	Black
Volume control:	Digital
International Protection (IP) code:	IP54

Ports & interfaces

Connectivity technology:	Wired & Wireless
3.5 mm connector:	N
2.5 mm connector:	N
USB connectivity:	Y
Bluetooth:	Y
Bluetooth version:	4.2
Wireless range:	30 m
Cable length:	1.5 m

Headphones

Ear coupling:	Intraaural
Headphone frequency:	150 - 6800 Hz

Headphone sensitivity:	27 dB
Driver unit:	15 mm
Driver type:	Dynamic
Noise reduction:	Y

Microphone

Noise-canceling:	Y
Microphone frequency:	150 - 6800 Hz

Battery

Talk time:	13 h
Continuous audio playback time:	14 h
Battery recharge time:	2 h

Operational conditions

Operating temperature (T-T):	-10 - 50 °C
------------------------------	-------------

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.