

Lenovo Flex System x240 M5 server (9532D2G)

Xeon 8C E5-2640v3 90W 2.6GHz/1866MHz/20MB, 1x16GB, O/Bay 2.5in SAS



Price details:

Price excl. VAT: 2,732.61 €

Eco fees: 0.07 €

VAT 21 %: 573.86 €

Product details:

Product code: 9532D2G

EAN: 5051045214643

Manufacturer: Lenovo

PDF generated on: 22 February, 2018



3,306.54 €

* VAT included

- Reduce operating costs with new energy-efficient Intel Xeon E5-2600v3 processors and 50 percent more cores and cache than the previous generation
- Industry-leading two-socket memory capacity, featuring TruDDR4 memory with up to 1.5 TB allowing for more VDI users or VMs per node
- Deploy new power for virtualization, performance and industry-leading networking flexibility
- Ideal platform for those migrating from BladeCenter® HS23 and competitive blade systems

As organizations face continued pressure to consolidate data center infrastructure, they also wrestle with the need to handle more compute-intensive workloads which are analyzing more data faster than ever before. With all these challenges to meet, there's never been a better time to choose the Flex System x240 M5 Compute Node to work within your Flex System or PureFlex environment.

- Optimized for virtualization, performance and highly scalable I/O
- Designed for simplified deployment and management
- Management of all resources from a single interface with FlexSystem Manager
- Virtual networking with integrated virtual fabric and up to 32 virtual networking ports

Hardware summary

- TruDDR4 Memory capacity up to 1.5 TB*
- Intel Xeon processor E5-2600 v3 product family
- Automated power management with onboard sensors
- Two 2.5-inch hot-swap disk slots
- Integrated system management
- Integrated RAID-0, -1
- Optional hypervisor
- 2 x Mezzanine Cards (x16 + x8 PCI Express 3.0)

Main specifications:

Processor

Processor frequency:	2.6 GHz
Processor family:	Intel Xeon E5 v3
Processor model:	E5-2640V3
Processor cores:	8
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	20 MB
System bus rate:	8 GT/s
Processor manufacturer:	Intel
Maximum number of SMP processors:	2
Processor socket:	LGA 2011 (Socket R)
Processor boost frequency:	3.40 GHz

Processor lithography:	22 nm
Processor threads:	16
Processor operating modes:	64-bit
Stepping:	R2
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Haswell
Tcase:	74.3 °C
Maximum internal memory supported by processor:	16 GB
Memory types supported by processor:	DDR4-SDRAM
Memory clock speeds supported by processor:	1600,1866 MHz
Memory bandwidth supported by processor (max):	59 GB/s
Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	40
PCI Express configurations:	x4, x8, x16
Processor package size:	52.5 mm
Supported instruction sets:	AVX
Processor code:	SR205
Scalability:	2S
Physical Address Extension (PAE):	Y
Physical Address Extension (PAE):	46 bit
Embedded options available:	Y
Thermal Design Power (TDP):	90 W
Processor series:	Intel Xeon E5-2600 v3
Conflict Free processor:	N

Memory

Internal memory:	16 GB
Maximum internal memory:	1536 GB
Memory slots:	24x DIMM
Memory clock speed:	1866 MHz
Memory layout (slots x size):	1 x 16 GB

Storage

Hard drive size:	2.5 "
Hard drive interface:	Serial ATA,Serial Attached SCSI (SAS)
RAID support:	Y
Maximum storage capacity:	4 TB
RAID levels:	0,1
Solid-state drive interface:	Serial ATA,Serial Attached SCSI

Networking

Ethernet LAN:	N
---------------	---

Ports & interfaces

USB 3.0 (3.1 Gen 1) Type-A ports quantity:	1
--	---

Expansion slots

PCI Express x16 (Gen 3.x) slots:	1
PCI Express slots version:	3.0

Design

Chassis type:	Rack
---------------	------

Performance

Operating system installed:	N
-----------------------------	---

Processor special features

CPU configuration (max):	2
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	N
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HTT):	Y

Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	N
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel® Secure Key:	Y
Intel TSX-NI:	N
Intel® OS Guard:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	N
Intel 64:	Y
Intel Identity Protection Technology version:	0.00
Intel Secure Key Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	0.00
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	83359

Weight & dimensions

Width:	215 mm
Depth:	493 mm
Height:	51 mm

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.