

# Lenovo System x3100 M4 server (2582ZEE)

Intel Xeon E3-1220 v2 (8M Cache, 3.10 GHz), 8GB DDR3 1600MHz, 2x 500GB HDD  
7200rpm, Gigabit Ethernet



## Price details:

Price excl. VAT: 1,434.33 €  
Eco fees: 0.07 €  
VAT 21 %: 301.22 €

## Product details:

Product code: 2582ZEE  
EAN: 5051045168038  
Manufacturer: Lenovo

PDF generated on: 23 February, 2018



**1,735.62 €**

\* VAT included

## Highlights.

- Delivers robust performance at a competitive entry-server price
- Offers flexibility in an optimized compact design
- Combines reliability and simple installation with innovative management technology

## Robust performance at an entry-level price.

With support for next-generation Intel Xeon and Core i3 processor technology, the IBM System x3100 M4 delivers strong performance for the price in a single-socket tower. Advanced features and functions, which come standard, include innovative integrated RAID capability, dependable server-class memory, energy efficiency, low-cost tower-to-rack kit and high-capacity storage options for enhanced availability.

## Ultra-small, flexible design

Extremely compact, the x3100 M4 fits easily in small spaces. Flexible, configure-to-order capabilities can provide the capacity and features you need, with multiple upgrade options to help meet future growth.

## Product features

- Generous server-class memory offers greater performance per price point.
- Support for up to four high-capacity, low-cost Serial ATA hard disk drives optimizes implementation flexibility.
- Three PCIe Gen 2 slots and a PCI Gen 3-ready slot offer ample I/O speed and an easy upgrade path.
- Integrated Management Module and full IBM toolbox simplify systems management.
- Embedded RAID support and optional advanced RAID upgrade facilitates enhanced availability and protection.
- Dual integrated Gigabit Ethernet offers greater network bandwidth.

## Main specifications:

### Processor

Processor frequency:	3.1 GHz
Processor family:	Intel Xeon E3 v2
Processor model:	E3-1220V2
Processor cores:	4
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	8 MB
System bus rate:	5 GT/s
Processor manufacturer:	Intel
Processor socket:	LGA 1155 (Socket H2)
Processor boost frequency:	3.5 GHz
Processor lithography:	22 nm
Processor threads:	4
Processor operating modes:	64-bit

Stepping:	E1
FSB Parity:	N
Bus type:	DMI
Processor codename:	Ivy Bridge
Tcase:	69.1 °C
Maximum internal memory supported by processor:	32 GB
Memory types supported by processor:	DDR3-SDRAM
Memory clock speeds supported by processor:	1333,1600 MHz
Memory bandwidth supported by processor (max):	25.6 GB/s
Memory channels supported by processor:	Dual
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	2
PCI Express configurations:	1x16+1x4,1x8+3x4,2x8+1x4
Processor package size:	37.5 mm
Supported instruction sets:	AVX,SSE4.1,SSE4.2
Processor code:	SR0PH
Embedded options available:	N
Thermal Design Power (TDP):	69 W
CPU multiplier (bus/core ratio):	31
Processor series:	Intel Xeon E3-1200 v2
Conflict Free processor:	N

#### Memory

Internal memory:	8 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	32 GB
Memory slots:	4x DIMM
Memory clock speed:	1600 MHz
ECC:	Y
Memory layout (slots x size):	2 x 4 GB

#### Storage

Total storage capacity:	1000 GB
Number of hard drives installed:	2
Hard drive size:	2.5 "
Hard drive interface:	Serial ATA
RAID support:	Y
Maximum storage capacity:	16 TB
Hard drive speed:	7200 RPM
Hard drive capacity:	500 GB
RAID levels:	0,1
Number of hard drives supported:	4
Supported hard disk drive sizes:	2.5 "
Hot-swap:	N
Supported storage drive interfaces:	SAS,Serial ATA

#### Graphics

Maximum graphics adapter memory:	16 MB
----------------------------------	-------

#### Networking

Ethernet LAN:	Y
Network ready:	Y
Networking features:	Gigabit Ethernet
Cabling technology:	10/100/1000Base-T(X)
Ethernet interface type:	Gigabit Ethernet

#### Ports & interfaces

USB 2.0 ports quantity:	6
VGA (D-Sub) ports quantity:	1
Ethernet LAN (RJ-45) ports:	2
Serial ports quantity:	1
Number of slots:	4

#### Expansion slots

PCI Express x1 slots:	1
PCI Express x4 slots:	1
PCI Express x8 slots:	1

PCI Express x16 slots:	1
PCI Express slots version:	3.0
<b>Design</b>	
Chassis type:	Tower (4U)
<b>Performance</b>	
Operating system installed:	N
Compatible operating systems:	Windows Server 2008/Server 2008 R2Red Hat LinuxSUSE Linux
Trusted Platform Module (TPM):	Y
Trusted Platform Module (TPM) version:	1.2
<b>Processor special features</b>	
CPU configuration (max):	1
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	N
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	N
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	N
Intel® Insider®:	N
Intel Flex Memory Access:	Y
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	N
Intel 64:	Y
Intel Identity Protection Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	0.00
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	Y
Processor ARK ID:	65734
<b>Power</b>	
Redundant power supply (RPS) support:	N
Number of power supply units:	1
Number of main power supplies:	1
<b>Certificates</b>	
Compliance industry standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
<b>Weight &amp; dimensions</b>	
Weight:	17300 g
<b>Other features</b>	
Mac compatibility:	N

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.