

## Lenovo System x3550 M5 server (5463F2G)

Xeon 8C E5-2640v3 90W 2.6GHz/1866MHz/20MB, 1x16GB, O/Bay HS 2.5in SATA/SAS, SR M5210, 550W p/s, Rack



### Price details:

Price excl. VAT: 3,607.06 €

Eco fees: 0.07 €

VAT 21 %: 757.50 €

### Product details:

Product code: 5463F2G

EAN: 5051045205269

Manufacturer: Lenovo

PDF generated on: 19 June, 2018



**4,364.63 €**

\* VAT included

- Optimize your workloads with choice of flexible storage-based configurations, designed for infrastructure basics to business-critical applications
- Reduce unplanned downtime and minimize costs with industry-leading reliability features and tools
- Safeguard enterprise data with built-in System x® Trusted Platform Assurance, an exclusive set of security features and practices, plus optional self-encrypting drives and IBM Security Key Lifecycle Manager
- Gain superior performance with Intel Xeon E5-2600 v3 processors (up to 36 cores per server), end-to-end 12 Gbps RAID support-devices and infrastructure
- Run up to 131 percent greater java workload performance,1 up to 61 percent greater virtualization performance,2 and up to 59 percent greater database performance3 per system than the previous generation
- Reduce data center costs with smart energy-efficient features, including unique 40° C operating temperature, Titanium power supplies (up to 96 percent efficiency), active/standby power supply modes, dual fan zone design, and TruDDR4 Memory (with up to 45 percent lower energy use over DDR3)4
- Run more virtual machines and workloads with up to 50 percent more cores and cache and 2x more memory capacity than previous generation

Designed in a compact, versatile 1U two-socket rack server, the System x3550 M5 rack server fuels almost any workload from infrastructure to high performance computing to Cloud or Big Data with leadership security, efficiency, and reliability. Integrated with up to two Intel E5-2600 v3 series CPUs with faster, energy-efficient TruDDR4 Memory, the x3550 M5 delivers exceptional performance. Storage can include up to 12 drives in an impressive selection of sizes and types.

Smart design adds flexibility for workload-tuned performance

The x3550 M5 incorporates energy smart features for minimized costs and efficient performance. Dual fan zones support operation in up to 40° C environments. Available 80 PLUS® Titanium power supply units (PSUs) can deliver 96 percent efficiency at 50 percent load. With twice the memory, up to 131 percent greater performance,1 and 50 percent more cores and cache per system than the previous generation, the x3550 M5 lets your workloads fly.

### Main specifications:

#### Processor

Processor frequency:	2.6 GHz
Processor family:	Intel Xeon E5 v3
Processor model:	E5-2640V3
Processor cores:	8
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	20 MB
System bus rate:	8 GT/s
Processor manufacturer:	Intel

Compatible processor series:	Intel Xeon
Processor socket:	LGA 2011 (Socket R)
Processor boost frequency:	3.40 GHz
Processor lithography:	22 nm
Processor threads:	16
Processor operating modes:	64-bit
Stepping:	R2
FSB Parity:	N
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Haswell
Tcase:	74.3 °C
Maximum internal memory supported by processor:	368 GB
Memory types supported by processor:	DDR4-SDRAM
Memory clock speeds supported by processor:	1600,1866 MHz
Memory bandwidth supported by processor (max):	59 GB/s
Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	40
PCI Express configurations:	x4, x8, x16
Processor package size:	52.5 mm
Supported instruction sets:	AVX
Processor code:	SR205
Scalability:	2S
Physical Address Extension (PAE):	Y
Physical Address Extension (PAE):	46 bit
Embedded options available:	Y
Thermal Design Power (TDP):	90 W
Processor series:	Intel Xeon E5-2600 v3
Conflict Free processor:	N

#### Memory

Internal memory:	16 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	1500 GB
Memory slots:	24
Memory clock speed:	1866 MHz
ECC:	Y
Memory layout (slots x size):	1 x 16 GB

#### Storage

Hard drive size:	2.5/3.5 "
Hard drive interface:	Serial ATA III,Serial Attached SCSI (SAS)
RAID support:	Y
RAID levels:	0,1,5,6,10,50,60
S.M.A.R.T. support:	Y
Solid-state drive interface:	Serial ATA III,Serial Attached SCSI
Hot-swap:	Y

#### Networking

Ethernet LAN:	Y
Cabling technology:	10/100/1000Base-T(X)
Ethernet interface type:	Fast Ethernet,Gigabit Ethernet

#### Ports & interfaces

Ethernet LAN (RJ-45) ports:	4
-----------------------------	---

#### Expansion slots

PCI Express slots version:	3.0
----------------------------	-----

#### Design

Chassis type:	Rack (1U)
Optical drive type:	N
Redundant fans support:	Y

#### Performance

Operating system installed:	N
Compatible operating systems:	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware vSphere

Trusted Platform Module (TPM):	Y
<b>Processor special features</b>	
CPU configuration (max):	2
Intel Rapid Storage Technology:	N
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	Y
Intel® Wireless Display (Intel® WiDi):	N
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Anti-Theft Technology (Intel® AT):	N
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® My WiFi Technology (Intel® MWT):	N
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	Y
Intel® Quick Sync Video Technology:	N
Intel® InTru® 3D Technology:	N
Intel® Clear Video HD Technology (Intel® CVT HD):	Y
Intel® Insider®:	N
Intel Flex Memory Access:	N
Intel® Smart Cache:	Y
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel® Secure Key:	Y
Intel TSX-NI:	N
Intel® OS Guard:	Y
Intel Clear Video Technology:	N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID):	Y
Intel 64:	Y
Intel Identity Protection Technology version:	0.00
Intel Secure Key Technology version:	1.00
Intel Virtualization Technology (VT-x):	Y
Intel TSX-NI version:	0.00
Intel Dual Display Capable Technology:	N
Intel FDI Technology:	N
Intel Fast Memory Access:	N
Processor ARK ID:	83359
<b>Power</b>	
Redundant power supply (RPS) support:	Y
Power supply:	550 W
Number of main power supplies:	1
<b>Weight &amp; dimensions</b>	
Width:	429 mm
Depth:	734 mm
Height:	43 mm

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.