

Lenovo System 3650 M5 server (5462Q2G)

1x E5-2697 v3 (14C, 2.6GHz, 35MB), 1x 16GB 2133MHz, M5210 + 2 GB Flash, O/Bay
2.5" HS SAS/SATA, 4x GbE, 1x 900W HS, 2U Rack



Price details:

Price excl. VAT: 6,525.48 €

Eco fees: 0.07 €

VAT 21 %: 1,370.37 €

Product details:

Product code: 5462Q2G

EAN: 7612392301103

Manufacturer: Lenovo

PDF generated on: 23 June, 2018



7,895.92 €

* VAT included

Fast Forward Your Business

- Versatile 2U 2-socket rack server runs 24/7
- 50% more cores to run more workloads
- Energy-efficient TruDDR4 Memory
- Flexible storage configurations
- Industry-leading security & reliability
- Reduced downtime & minimized costs

Highlights

- Tackle enterprise workloads with power, efficiency, and reliability
- Choose from flexible storage configurations for workload-optimized performance
- Reduce unplanned downtime and minimize costs
- Gain superior performance with Intel® Xeon® E5-2600 v3 processors (up to 36 cores per server), end-to-end 12 Gbps RAID support-devices and infrastructure-up to four RAID adapters, and up to two 300 W GPUs
- Run up to 131 percent greater java workload performance, up to 61 percent greater virtualization performance, and up to 59 percent greater database performance per system than the previous generation
- Reduce data-center costs with smart energy-efficient features, including unique 40° C operating temperature, 80 PLUS® Titanium power supplies (up to 96 percent efficiency), active/standby power supply modes, dual fan zone design, and TruDDR4 Memory (up to 45 percent lower energy use over DDR3)
- Run more virtual machines and workloads with up to 50 percent more cores and cache and 2x more memory capacity per system than previous generation
- Simplify server management and administration with Lenovo XClarity

With the powerful, versatile 2U dual-socket System x3650 M5 rack server, you can run even more workloads, 24/7, and gain faster business insights. Integrated with up to two Intel® Xeon® processors E5-2600 v3 series and faster TruDDR4 Memory, the x3650 M5 fast forwards your business. You can select from an impressive array of storage configurations (up to 26 drive bays) that optimize diverse workloads from cloud to big data.

Main specifications:

Processor

| | |
|---------------------------------|------------------|
| Processor frequency: | 2.6 GHz |
| Processor family: | Intel Xeon E5 v3 |
| Processor model: | E5-2697V3 |
| Processor cores: | 14 |
| Number of processors installed: | 1 |
| Processor cache type: | Smart Cache |
| Processor cache: | 35 MB |

| | |
|---|------------------------|
| System bus rate: | 9.6 GT/s |
| Processor manufacturer: | Intel |
| Maximum number of SMP processors: | 2 |
| Processor socket: | LGA 2011-v3 |
| Motherboard chipset: | Intel C612 |
| Supported processor sockets: | LGA 2011-v3 (Socket R) |
| Processor boost frequency: | 3.6 GHz |
| Processor lithography: | 22 nm |
| Processor threads: | 28 |
| Processor operating modes: | 64-bit |
| Stepping: | C1 |
| FSB Parity: | N |
| Bus type: | QPI |
| Number of QPI links: | 2 |
| Processor codename: | Haswell |
| Tcase: | 76.7 °C |
| Maximum internal memory supported by processor: | 768 GB |
| Memory types supported by processor: | DDR4-SDRAM |
| Memory clock speeds supported by processor: | 1600,1866,2133 MHz |
| Memory bandwidth supported by processor (max): | 68 GB/s |
| Memory channels supported by processor: | Quad |
| ECC supported by processor: | Y |
| Execute Disable Bit: | Y |
| Idle States: | Y |
| Thermal Monitoring Technologies: | Y |
| Maximum number of PCI Express lanes: | 40 |
| PCI Express configurations: | x4, x8, x16 |
| Processor package size: | 52.5 mm |
| Supported instruction sets: | AVX 2.0 |
| Scalability: | 2S |
| Physical Address Extension (PAE): | 46 bit |
| Embedded options available: | N |
| Thermal Design Power (TDP): | 145 W |
| Processor series: | Intel Xeon E5-2600 v3 |
| Conflict Free processor: | N |

Memory

| | |
|-------------------------------|------------|
| Internal memory: | 16 GB |
| Internal memory type: | DDR4-SDRAM |
| Maximum internal memory: | 1500 GB |
| Memory slots: | 24 |
| Memory clock speed: | 2133 MHz |
| ECC: | Y |
| Memory layout (slots x size): | 1 x 16 GB |

Storage

| | |
|-------------------------------------|---|
| Hard drive size: | 2.5 " |
| Hard drive interface: | Serial ATA III,Serial Attached SCSI (SAS) |
| RAID support: | Y |
| Maximum storage capacity: | 100 TB |
| Hot-Plug support: | Y |
| Supported hard disk drive sizes: | 2.5,3.5 " |
| Hot-swap: | Y |
| Supported storage drive interfaces: | SAS-2,Serial ATA III |

Graphics

| | |
|----------------------------------|-------|
| Maximum graphics adapter memory: | 16 MB |
|----------------------------------|-------|

Networking

| | |
|--------------------------|----------------------|
| Ethernet LAN: | Y |
| Cabling technology: | 10/100/1000Base-T(X) |
| Ethernet interface type: | Gigabit Ethernet |

Ports & interfaces

| | |
|--|---|
| USB 2.0 ports quantity: | 4 |
| VGA (D-Sub) ports quantity: | 2 |
| Ethernet LAN (RJ-45) ports: | 4 |
| USB 3.0 (3.1 Gen 1) Type-A ports quantity: | 3 |

Expansion slots

PCI Express x8 (Gen 3.x) slots: 1
PCI Express slots version: 3.0

Design

Chassis type: Rack (2U)
Rack mounting: Y

Performance

Operating system installed: N
Compatible operating systems: Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware vSphere
Trusted Platform Module (TPM): Y
Trusted Platform Module (TPM) version: 2.0

Processor special features

Intelligent Platform Management Interface (IPMI) support: Y
CPU configuration (max): 2
Intel Rapid Storage Technology: N
Enhanced Intel SpeedStep Technology: Y
Intel® Identity Protection Technology (Intel® IPT): N
Intel® Wireless Display (Intel® WiDi): N
Intel Virtualization Technology for Directed I/O (VT-d): Y
Intel® Anti-Theft Technology (Intel® AT): N
Intel® Hyper Threading Technology (Intel® HT Technology): Y
Intel® My WiFi Technology (Intel® MWT): N
Intel® Turbo Boost Technology: 2.0
Intel® vPro® Technology: Y
Intel® Quick Sync Video Technology: N
Intel® InTru® 3D Technology: N
Intel® Clear Video HD Technology (Intel® CVT HD): N
Intel® Insider®: N
Intel Flex Memory Access: N
Intel® Smart Cache: Y
Intel® AES New Instructions (Intel® AES-NI): Y
Intel Trusted Execution Technology: Y
Intel VT-x with Extended Page Tables (EPT): Y
Intel Demand Based Switching: Y
Intel® Secure Key: Y
Intel TSX-NI: N
Intel® OS Guard: Y
Intel Clear Video Technology: N
Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID): N
Intel 64: Y
Intel Identity Protection Technology version: 0.00
Intel Secure Key Technology version: 1.00
Intel Virtualization Technology (VT-x): Y
Intel TSX-NI version: 0.00
Intel Dual Display Capable Technology: N
Intel FDI Technology: N
Intel Fast Memory Access: N
Processor ARK ID: 81059

Power

Redundant power supply (RPS) support: Y
Power supply: 900 W
Number of redundant power supplies supported: 2
Number of main power supplies: 1

Operational conditions

Operating temperature (T-T): 5 - 40 °C
Storage temperature (T-T): 5 - 45 °C
Operating relative humidity (H-H): 8 - 85 %
Storage relative humidity (H-H): 8 - 85 %
Operating altitude: 0 - 3050 m

Certificates

Energy Star certified: Y

Weight & dimensions

Width: 445.6 mm
Depth: 800 mm

Height: 86.5 mm
Weight: 34000 g

Packaging content

Cables included: AC

Other features

Graphics adapter: G200eR2
Graphics adapter family: Matrox
Intel® Virtualization Technology (Intel® VT): VT-d,VT-x