

Lenovo System x3550 M5 server (8869EKG)

Intel Xeon E5-2630 v4(25M Cache, 2.20 GHz), 16GB DDR3 2133MHz, Raid M5210-e, 4 x 2.5" Hot swap SATA/SAS, 4 x GbE, 1 x 750W redundant hot-swap



Price details:

Price excl. VAT: 2,667.03 €

Eco fees: 0.07 €

VAT 21 %: 560.09 €

Product details:

Product code: 8869EKG

EAN: 0889488407484

Manufacturer: Lenovo

PDF generated on: 22 February, 2018



3,227.19 €

* VAT included

- Optimize your workloads with choice of flexible storage-based configurations, designed for infrastructure basics to business-critical applications
- Reduce unplanned downtime and minimize costs with industry-leading reliability features and tools
- Safeguard enterprise data with built-in System x® Trusted Platform Assurance, an exclusive set of security features and practices, plus optional self-encrypting drives and IBM Security Key Lifecycle Manager
- Gain superior performance with Intel Xeon E5-2600 v3 processors (up to 36 cores per server), end-to-end 12 Gbps RAID support-devices and infrastructure
- Run up to 131 percent greater java workload performance, up to 61 percent greater virtualization performance, and up to 59 percent greater database performance per system than the previous generation
- Reduce data center costs with smart energy-efficient features, including unique 40° C operating temperature, Titanium power supplies (up to 96 percent efficiency), active/standby power supply modes, dual fan zone design, and TruDDR4 Memory (with up to 45 percent lower energy use over DDR3)
- Run more virtual machines and workloads with up to 50 percent more cores and cache and 2x more memory capacity than previous generation
- Designed in a compact, versatile 1U two-socket rack server, the System x3550 M5 rack server fuels almost any workload from infrastructure to high performance computing to Cloud or Big Data with leadership security, efficiency, and reliability. Integrated with up to two Intel E5-2600 v3 series CPUs with faster, energy-efficient TruDDR4 Memory, the x3550 M5 delivers exceptional performance. Storage can include up to 12 drives in an impressive selection of sizes and types.

Smart design adds flexibility for workload-tuned performance

The x3550 M5 incorporates energy smart features for minimized costs and efficient performance. Dual fan zones support operation in up to 40° C environments. Available 80 PLUS® Titanium power supply units (PSUs) can deliver 96 percent efficiency at 50 percent load. With twice the memory, up to 131 percent greater performance, and 50 percent more cores and cache per system than the previous generation, the x3550 M5 lets your workloads fly.

Main specifications:

Processor

Processor frequency:	2.2 GHz
Processor family:	Intel Xeon E5 v4
Processor model:	E5-2630V4
Processor cores:	10
Number of processors installed:	1
Processor cache type:	Smart Cache
Processor cache:	25 MB
System bus rate:	8 GT/s
Processor socket:	LGA 2011-v3
Processor boost frequency:	3.1 GHz

Processor lithography:	14 nm
Processor threads:	20
Processor operating modes:	64-bit
Stepping:	R0
Bus type:	QPI
Number of QPI links:	2
Processor codename:	Broadwell
Tcase:	74 °C
Maximum internal memory supported by processor:	1536 GB
Memory types supported by processor:	DDR4-SDRAM
Memory clock speeds supported by processor:	1600,1866,2133 MHz
Memory bandwidth supported by processor (max):	69.3 GB/s
Memory channels supported by processor:	Quad
ECC supported by processor:	Y
Execute Disable Bit:	Y
Idle States:	Y
Thermal Monitoring Technologies:	Y
Maximum number of PCI Express lanes:	40
Processor package size:	52.5 x 51 mm
Supported instruction sets:	AVX 2.0
Processor code:	SR2R7
Scalability:	2S
Physical Address Extension (PAE):	Y
Physical Address Extension (PAE):	46 bit
Embedded options available:	N
Thermal Design Power (TDP):	85 W
Processor series:	Intel Xeon E5-2600 v4
Conflict Free processor:	Y

Memory

Internal memory:	16 GB
Internal memory type:	DDR4-SDRAM
Maximum internal memory:	384 GB
Memory slots:	24
Memory clock speed:	2133 MHz
ECC:	Y
Memory layout (slots x size):	1 x 16 GB

Storage

Hard drive size:	2.5 "
Hard drive interface:	Serial ATA III,Serial Attached SCSI (SAS)
RAID support:	Y
RAID levels:	0,10
Number of hard drives supported:	4
S.M.A.R.T. support:	Y
Supported hard disk drive sizes:	2.5 "
Solid-state drive interface:	Serial ATA III,Serial Attached SCSI
Hot-swap:	Y

Graphics

Maximum graphics adapter memory:	16 MB
On-board graphics adapter:	Y

Networking

Ethernet LAN:	Y
LAN controller:	Broadcom BCM5719
Cabling technology:	10/100/1000Base-T(X)
Ethernet interface type:	Fast Ethernet,Gigabit Ethernet

Ports & interfaces

USB 2.0 ports quantity:	2
VGA (D-Sub) ports quantity:	2
Ethernet LAN (RJ-45) ports:	4
Serial ports quantity:	1
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	3

Expansion slots

PCI Express x8 (Gen 3.x) slots:	1
PCI Express slots version:	3.0

Design

Chassis type:	Rack (1U)
Optical drive type:	N
Performance	
Operating system installed:	N
Compatible operating systems:	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware vSpher
Trusted Platform Module (TPM):	Y
Processor special features	
CPU configuration (max):	2
Enhanced Intel SpeedStep Technology:	Y
Intel® Identity Protection Technology (Intel® IPT):	Y
Intel Virtualization Technology for Directed I/O (VT-d):	Y
Intel® Hyper Threading Technology (Intel® HT Technology):	Y
Intel® Turbo Boost Technology:	2.0
Intel® vPro® Technology:	Y
Intel Flex Memory Access:	N
Intel® AES New Instructions (Intel® AES-NI):	Y
Intel Trusted Execution Technology:	Y
Intel Enhanced Halt State:	Y
Intel VT-x with Extended Page Tables (EPT):	Y
Intel Demand Based Switching:	Y
Intel® Secure Key:	Y
Intel TSX-NI:	Y
Intel® OS Guard:	Y
Intel 64:	Y
Intel Virtualization Technology (VT-x):	Y
Processor ARK ID:	92981
Power	
Redundant power supply (RPS) support:	Y
Power supply:	750 W
Number of redundant power supplies supported:	2
Number of main power supplies:	1
Weight & dimensions	
Width:	429 mm
Depth:	734 mm
Height:	43 mm
Weight:	13800 g
Other features	
Graphics adapter:	G200eR2
Graphics adapter family:	Matrox

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.