

Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

PDF generated on: 13 December, 2018

Polycom VVX 300 IP phone (2200-46135-025)

Polycom VVX 300, Fast Ethernet, PoE

Price details:

Price excl. VAT: 81.12 € Eco fees: 0.00 € VAT 21 %: 17.04 €

Product details: Product code: 2200-46135-025

EAN: 0610807774686 Manufacturer: Polycom

98.16 €

* VAT included



These powerful 6-line entry-level Business Media Phones are for today's cubicle workers that handle a low to moderate volume of calls and need crystal clear communications.

Give your cubicle worker the best experience with this high quality UC Business Media Phone. Designed for a broad range of environments for small and medium businesses.

- Make more efficient and productive calls with the unparalleled voice clarity of Polycom HD Voice
- Improve productivity for cubicle worker's and call center operators through an intuitive easy to use user interface
- Reduce deployment and maintenance costs-the Polycom Zero Touch Provisioning and web based configuration tool makes the VVX 300 simple to deploy, easy to administer, upgrade, and maintain
- Leverage previous IT infrastructure investments-deploy VVX 300 business media phones on your existing network without needing to upgrade your call control platform
- Easily to integrate with third- party web-based UC and productivity applications for broad, standards based, open APIs

Main specifications:

Features

Colour of product: Black

Handset type: Wired handset

Expansion module support: Y
Unicode UTF-8 character support: Y
Ethernet cable: Y
Internet connection required: Y

Display

Touchscreen: N
Display: LCD

Display resolution: 208 x 104 pixels

Backlight display:

Phone features

6 lines Lines quantity: Caller ID: Υ Call waiting: Υ Speed dialing: Υ Call hold: Call forwarding: Υ Conference call: Υ Redialing: Do not disturb function: Full duplex:

Audio

Speakerphone: Y

Networking

Ethernet LAN: Y
Wi-Fi: N
Bluetooth: N
Quality of Service (QoS) support: Y

Ports & interfaces

Ethernet LAN (RJ-45) ports: 2 RJ-9 ports quantity: 1

Power

Power over Ethernet (PoE):

Security

Security algorithms: HTTPS,SRTP,SSL/TLS

Weight & dimensions

 Width:
 304.8 mm

 Depth:
 209.5 mm

 Height:
 107.9 mm

 Weight:
 900 g

Operational conditions

Operating temperature (T-T): 0 - 40 °C
Operating relative humidity (H-H): 5 - 95 %
Storage temperature (T-T): -40 - 70 °C

Packaging content

Number of handles included: 1 pc(s)

^{*}PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herin, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.