

Polycom CX5100 video conferencing system (2200-63890-101)

1080p, 360°, 160Hz - 22kHz, 88dBA, RJ-45 10/100/1000 Mbit, USB 2.0, USB 3.0



Price details:

Price excl. VAT: 4,658.20 €

Eco fees: 0.04 €

VAT 21 %: 978.23 €

Product details:

Product code: 2200-63890-101

EAN: 0610807784029

Manufacturer: Polycom

5,636.47 €

* VAT included

PDF generated on: 19 October, 2018

CX5100 Unified Conference Station for Microsoft Lync, USB only. Includes power-data box, cables, documentation and European Power Cord.

The IT department's challenge is to make video meetings in conference rooms more effective, reduce video support calls and eliminate the need for "in room" video support services to get video meetings started. Are your video conference room users distracted by video or audio quality issues? Are they having trouble seeing or identifying who is speaking? Are they finding it hard to pan the camera to focus attention on the active speaker? Are they frustrated by trying to learn another user interface? Solve these challenges and video conference room use goes up. More room use translates to fully realizing the benefits of video collaboration and achieving your expected return on investment. For Skype for Business and Microsoft® Lync® users, the Polycom® CX5100 unified conference station answers these challenges with a truly unique around-the-table video collaboration solution.

More productive meetings

The Polycom CX5100 unified conference station brings the powerful collaboration capabilities of voice, video and content together through a unique 360-degree panoramic view of the entire room. A second HD video view of the active speaker is also sent at 1080p video resolution using advanced technology that automatically focuses on the current speaker and tracks the flow of conversation to enable richer, more interactive communication. No more reaching for a video control device. It's a "hands-free" experience that allows you to forget about the technology and simply focus on your meeting.

Easy to deploy and use

An intuitive design with full plug-and-play functionality makes it easy to deploy and use the Polycom CX5100. With little or no training, anyone with a laptop that has Skype for Business or Microsoft Lync can walk into the room and simply plug the CX5100 unified conference station into their PC's USB port and start sharing voice and 360-degree panorama video. Control, invitations, and content sharing are handled through the familiar Skype for Business user interface your users already know and use every day. Removing the challenge of learning a remote control device means fewer support calls and fewer requests for "white glove" level support from the IT department.

Audio quality matters

The Polycom CX5100 unified conference station features Polycom's legendary audio, bringing the industry's best voice quality to your Skype for Business meeting with a dynamic range of 160 Hz to 22,000 Hz. Polycom® HD Voice and a microphone range of 20 feet (6 meters) means everyone in the room can be clearly heard, even at the end of the table. Optional extension microphones extend the range even further, if needed. While the CX5100 is a USB-only model, for customers needing standalone SIP VoIP for audio conferences, the Polycom® CX5500 unified conference station adds SIP telephony, eliminating the need to install a separate audio conference station in the room.

Main specifications:

Technical details

Product type:

Group video conferencing system

Colour of product:	Black
Video	
HD type:	Full HD
Megapixel:	2 MP
Supported video modes:	1080p
Supported graphics resolutions:	352 x 288,640 x 480 (VGA),1056 x 144,1280 x 720 (HD 720),1920 x 1080 (HD 1080)
Audio	
Frequency range:	160 - 22000 Hz
Ports & interfaces	
USB 2.0 ports quantity:	1
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	1
Ethernet LAN (RJ-45) ports:	1
Networking	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	15 - 85 %
Storage temperature (T-T):	-40 - 60 °C
Power	
AC input voltage:	100 - 240 V
AC input frequency:	50/60 Hz
Power consumption (typical):	110 W
Weight & dimensions	
Width:	369 mm
Depth:	325 mm
Height:	348 mm
Weight:	2300 g
Package width:	520 mm
Package depth:	430 mm
Package height:	430 mm
Package weight:	9070 g

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.