

Polycom VVX 101 IP phone (2200-40250-025)

1 line, LCD, G.722, 1/10 ethernet port



Price details:

Price excl. VAT: 52.31 €

Eco fees: 0.30 €

VAT 21 %: 11.05 €

Product details:

Product code: 2200-40250-025

EAN: 0610807829638

Manufacturer: Polycom

63.66 €

* VAT included

PDF generated on: 15 December, 2018

The Polycom VVX 101 business media phone is a one-line SIP phone for a home office or shared/common areas delivering enterprise grade sound quality

- Use the VVX 101 as a simple, one line phone for home office or shared/common-areas
- Make more efficient and productive calls with unparalleled voice clarity
- Deploy in hosted or premise-based environments
- Reduce deployment and maintenance costs-the Polycom Zero Touch Provisioning and web-based configuration tool makes the VVX 101 simple to deploy, easy to administer, upgrade, and maintain
- Leverage previous IT infrastructure investments-deploy VVX 101 business media phones on your existing network without needing to upgrade your call control platform

Main specifications:

Features

| | |
|---|---------------|
| Colour of product: | Black |
| Handset type: | Wired handset |
| Unicode UTF-8 character support: | Y |
| Volume control: | Digital |
| Integrated voicemail: | Y |
| Dual-Tone Multi-Frequency (DTMF) modes: | In-band |
| SIP registrar server: | Y |

Display

| | |
|---------------------|-----------------|
| Touchscreen: | N |
| Display: | LCD |
| Display resolution: | 132 x 64 pixels |
| Display diagonal: | 2.5 " |
| Backlight display: | Y |

Phone features

| | |
|--------------------------|---------|
| Lines quantity: | 1 lines |
| Call waiting: | Y |
| Distinctive ring: | Y |
| Speed dialing: | Y |
| Call hold: | Y |
| Call forwarding: | Y |
| Conference call: | Y |
| Redialing: | Y |
| Do not disturb function: | Y |
| Call pick up: | Y |
| Call transfer: | Y |

Audio

| | |
|------------------------------------|---|
| Speakerphone: | Y |
| Voice codecs: | G.711,G.722,G.729ab |
| Noise reduction: | Y |
| Echo cancellation: | Y |
| Voice activity detection: | Y |
| Adaptive jitter buffers: | Y |
| Frequency range: | 150 - 7000 Hz |
| Networking | |
| Ethernet LAN: | Y |
| Wi-Fi: | N |
| Ethernet LAN interface type: | Fast Ethernet |
| Ethernet LAN data rates: | 10,100 Mbit/s |
| Quality of Service (QoS) support: | Y |
| DHCP client: | Y |
| Event logging: | Y |
| Syslog: | Y |
| Auto diagnostic: | Y |
| Ports & interfaces | |
| Ethernet LAN (RJ-45) ports: | 1 |
| RJ-9 ports quantity: | 1 |
| DC-in jack: | Y |
| WAN connection type: | RJ-45 |
| Camera | |
| Built-in camera: | N |
| Power | |
| Power over Ethernet (PoE): | Y |
| Weight & dimensions | |
| Width: | 170 mm |
| Depth: | 180 mm |
| Height: | 150 mm |
| Weight: | 800 g |
| Certificates | |
| Safety: | UL 60950-1 , CE Mark , CAN/CSA C22.2 No 60950-1 , EN 60950-1 , IEC 60950-1 , AS/NZS 60950-1 |
| Operational conditions | |
| Operating temperature (T-T): | 0 - 40 °C |
| Operating relative humidity (H-H): | 5 - 95 % |
| Storage temperature (T-T): | -40 - 70 °C |
| Packaging content | |
| Number of handles included: | 1 pc(s) |
| Quick start guide: | Y |
| Cables included: | LAN (RJ-45) |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.