

Polycom VVX 300 IP phone (2200-46135-019)

VVX 300 Skype for Business, POE



Price details:

Price excl. VAT: 87.59 €

Eco fees: 0.30 €

VAT 21 %: 18.46 €

Product details:

Product code: 2200-46135-019

EAN: 0610807849247

Manufacturer: Polycom

106.35 €

* VAT included

PDF generated on: 12 December, 2018

Powerful entry-level business media phones for today's cubicle workers handling a low to moderate volume of calls delivering crystal clear communications

The Polycom® VVX® 300 Series are expandable business media phones that deliver crystal clear communications, enhanced collaboration and personal productivity.

Simplicity and ease of use

The VVX 300 Series brings high-quality, cost-effective solutions to any environment through advanced unified communications (UC) features. The intuitive user interface of the VVX 300 Series makes usability and navigation easy and requires minimal training.

Unsurpassed voice quality and clarity

The VVX 300 Series delivers breakthrough Polycom® HD Voice quality for lifelike conversations while minimizing fatigue, making calls more efficient and productive.

Maximize productivity

Give your front-line workers the best experience with this high-quality 6-line business media phone. The VVX 300 Series improves personal productivity by complementing the workplace applications on their computer. Users can view and manage their Microsoft Exchange Calendars, receive meeting reminders and alerts, access the corporate directory and instant messaging/presence status right on their phone display, even while waiting for their PC to boot. They can also extend their PC's desktop to include the VVX 300 Series screen for mouse/keyboard navigation and interaction.

Best-in-class deployment and administration

The VVX 300 Series is easy to deploy and simple to manage. Using an enterprise-grade, Web-based configuration method allows administrators to easily provision and maintain even a large number of phones throughout the entire organization.

Customizable and expandable

The VVX 300 Series provides personalized information at a glance, through built-in Web applications and custom backgrounds. The VVX 300 Series also comes ready for future expansion modules as your users' needs and business grows.

Market-leading open standards interoperability

Designed for enhanced interoperability, the VVX 300 Series leverages and complements the other existing IT investments in your business. With the broadest call server interoperability in the industry, the Polycom VVX 300 entry-level business media phone can become the flexible and future-proof foundation for any organization's UC strategy

Main specifications:

Features

Colour of product:	Black
Handset type:	Wired handset
Expansion module support:	Y
Unicode UTF-8 character support:	Y
Keypad number of keys:	12
Ethernet cable:	Y
Headset connectivity:	RJ-9
Volume control:	Digital
Integrated voicemail:	Y

Display

Touchscreen:	N
Display:	LCD
Display resolution:	208 x 104 pixels
Backlight display:	Y
Display number of colours:	Monochrome

Phone features

Lines quantity:	6 lines
Caller ID:	Y
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
On-hook dialing:	Y
Call transfer:	Y

Audio

Speakerphone:	Y
Microphone mute:	Y
Voice codecs:	G.711,G.722,G.722.1,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Frequency range:	150 - 7000 Hz

Networking

Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	FTP/TFTP/HTTP/HTTPS/IPv4/TCP
Quality of Service (QoS) support:	Y
DHCP client:	Y
VoIP protocols:	SIP, SDP, IETF SIP
Networking standards:	IEEE 802.3

Ports & interfaces

Ethernet LAN (RJ-45) ports:	2
RJ-9 ports quantity:	1
DC-in jack:	Y

Camera

Built-in camera:	N
------------------	---

Power

Power over Ethernet (PoE):	Y
Power consumption (typical):	12 W

Weight & dimensions

Width:	190 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g

Package width:	290 mm
Package depth:	200 mm
Package height:	90 mm
Package weight:	1400 g

Operational conditions

Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C

Packaging content

Number of handles included:	1 pc(s)
Quick start guide:	Y
Manual:	Y
Cables included:	LAN (RJ-45)