

# Polycom VVX 410 Skype for Business IP phone (2200-46162-019)

Business Media Phone, 12-Line, HD Voice, 2 x Gigabit Ethernet RJ-45, 8.89 cm (3.5")  
TFT (320 x 240), PoE



## Price details:

Price excl. VAT: 137.05 €

Eco fees: 0.30 €

VAT 21 %: 28.84 €

## Product details:

Product code: 2200-46162-019

EAN: 0610807849278

Manufacturer: Polycom

**166.19 €**

\* VAT included

PDF generated on: 10 December, 2018

These color 12-line mid-range Business Media Phones are for today's office workers and call attendants who depend on crystal clear communications

Give your call attendant a high-quality, cost effective UC solution that will handle their moderate call volume and provide them with the advanced telephony features they expect from a modern media phone.

- Make more efficient and productive calls with the unparalleled voice clarity of Polycom HD Voice
- Improve productivity for office staff and cubicle worker's via an intuitive larger, color display and easy to use line appearances
- Reduce deployment and maintenance costs-the Polycom Zero Touch Provisioning and web based configuration tool makes the VVX 400 series simple to deploy, easy to administer, upgrade, and maintain
- Leverage previous IT infrastructure investments-deploy VVX 400 series business media phones on your existing network without needing to upgrade your call control platform
- Easily integrate with third- party UC and productivity applications for broad, standards-based, open APIs

## Main specifications:

### Features

Colour of product:	Black
Handset type:	Wired handset
Expansion module support:	Y
Unicode UTF-8 character support:	Y
Ethernet cable:	Y
Data transfer rate:	1000 Mbit/s
Integrated voicemail:	Y
Dual-Tone Multi-Frequency (DTMF) modes:	In-band

### Display

Touchscreen:	N
Display:	TFT
Display resolution:	320 x 240 pixels
Display diagonal:	3.5 "
Backlight display:	Y

### Phone features

Lines quantity:	12 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y

Call hold:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y
Call transfer:	Y
<b>Audio</b>	
Speakerphone:	Y
Microphone mute:	Y
Voice codecs:	G.711,G.722.1,G.729ab,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Frequency range:	150 - 7000 Hz
Comfort noise generation (CNG):	Y
<b>Networking</b>	
Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	FTP/TFTP/HTTP/HTTPS
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Networking standards:	IEEE 802.1Q,IEEE 802.1p,IEEE 802.1x,IEEE 802.3,IEEE 802.3ab,IEEE 802.3af,IEEE 802.3u
Auto diagnostic:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	1
RJ-9 ports quantity:	1
<b>Camera</b>	
Built-in camera:	N
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	802.1x RADIUS
<b>Weight &amp; dimensions</b>	
Width:	190 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g
Package width:	291 mm
Package depth:	200 mm
Package height:	97 mm
Package weight:	1400 g
<b>Certificates</b>	
Certification:	FCC Part 15 (CFR 47) Class BICES-003 Class BEN55022 Class BCISPR22 Class BVCCI Class BEN55024EN61000-3-2; EN61000-3-3NZ TelepermitKorea KC 3UAE TRARussia CUBrazil ANATEL 3Australia RCM
Compliance industry standards:	ROHS
Skype:	Y
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
<b>Packaging content</b>	
Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.