

# Polycom VVX 201 IP phone (2200-40450-019)

Business Media Phone, 2-Line, 2 x Fast Ethernet RJ-45, LCD 132x64



## Price details:

Price excl. VAT: 68.68 €

Eco fees: 0.30 €

VAT 21 %: 14.49 €

## Product details:

Product code: 2200-40450-019

EAN: 0610807849131

Manufacturer: Polycom

**83.47 €**

\* VAT included

PDF generated on: 10 December, 2018

Entry-level Two-line IP phone with HD sound quality and 2 Ethernet ports

The Polycom VVX 201 business media phone is a two-line SIP phone designed for small businesses and medium-sized organizations delivering HD Voice technology and a wide range of business telephony features.

- Use the VVX 201 is a basic two line desk phone for call centers, retail environments and for shared/common-areas
- Make more efficient and productive calls with Polycom's HD Voice technology
- Deploy the VVX 201 in hosted or premise-based environments
- Reduce deployment and maintenance costs-the Polycom Zero Touch Provisioning and web-based configuration tool makes the VVX 201 simple to deploy, easy to administer, upgrade, and maintain
- Leverage previous IT infrastructure investments-deploy VVX 201 business media phones on your existing network without needing to upgrade your call control platform

## Main specifications:

### Features

Product colour:	Black
Handset type:	Wired handset
Expansion module support:	N
Unicode UTF-8 character support:	Y
Wall mountable:	Y
Backlight colour:	Blue
Firmware upgradeable:	Y
Data transfer rate:	100 Mbit/s
Mounting:	Desk/Wall
Integrated voicemail:	Y

### Display

Touchscreen:	N
Display:	LED
Display resolution:	132 x 64 pixels
Display diagonal:	2.5 "
Display number of colours:	Monochrome

### Phone features

Lines quantity:	2 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y

Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y
Full duplex:	Y
Call transfer:	Y
<b>Audio</b>	
Speakerphone:	Y
Microphone mute:	Y
Voice codecs:	G.711,G.722,G.729ab,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Frequency range:	150 - 7000 Hz
<b>Video</b>	
Video call:	N
<b>Networking</b>	
Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	FTP/FTPS/TFTP/HTTP/HTTPS
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Networking standards:	IEEE 802.1Q,IEEE 802.1p,IEEE 802.1x,IEEE 802.3,IEEE 802.3af,IEEE 802.3u
Auto diagnostic:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
RJ-9 ports quantity:	1
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	802.1x RADIUS,HTTPS,SSL/TLS
Password protection type:	User
<b>Weight &amp; dimensions</b>	
Width:	170 mm
Depth:	180 mm
Height:	150 mm
Weight:	800 g
<b>Certificates</b>	
Safety:	UL 60950-1, CE Mark, CAN/CSA C22.2 No 60950-1, EN 60950-1, IEC 60950-1, AS/NZS 60950-1
Certification:	FCC Part 15 (CFR 47) Class B, ICES-003 Class B, EN55022 Class B, CISPR22 Class B, VCCI Class B, EN55024, EN61000-3-2, EN61000-3-3, NZ Telepermit, UAE TRA, Australia RCM, ROHS, CITC, ANATEL,Customs Union, KCC, TAA, CCC
Skype:	Y
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
<b>Other features</b>	
Backlight:	Y
<b>Packaging content</b>	
Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.