

# Polycom VVX 311 IP phone (2200-48350-025)

6-line, LCD 208x104, 2xEthernet 10/100, HD Voice, PoE, black



## Price details:

Price excl. VAT: 99.02 €

Eco fees: 0.30 €

VAT 21 %: 20.86 €

## Product details:

Product code: 2200-48350-025

EAN: 0610807846772

Manufacturer: Polycom

**120.18 €**

\* VAT included

PDF generated on: 15 December, 2018

These powerful 6-line entry-level Business Media Phones are for today's cubicle workers that handle a low to moderate volume of calls and need crystal clear communications.

Give your cubicle worker the best experience with this high quality UC Business Media Phone. Designed for a broad range of environments for small and medium businesses.

- Make more efficient and productive calls with the unparalleled voice clarity of Polycom HD Voice
- Improve productivity for cubicle worker's and call center operators through an intuitive easy to use user interface
- Reduce deployment and maintenance costs-the Polycom Zero Touch Provisioning and web based configuration tool makes the VVX 300 series simple to deploy, easy to administer, upgrade, and maintain
- Leverage previous IT infrastructure investments-deploy VVX 300 series business media phones on your existing network without needing to upgrade your call control platform
- Easily to integrate with third- party web-based UC and productivity applications for broad, standards based, open APIs

## Main specifications:

### Features

Colour of product:	Black
Handset type:	Wired handset
Unicode UTF-8 character support:	Y
Backlight colour:	Blue
Volume control:	Digital
Dual-Tone Multi-Frequency (DTMF) modes:	In-band
SIP registrar server:	Y

### Display

Touchscreen:	N
Display:	LCD
Display resolution:	208 x 104 pixels
Display diagonal:	3.2 "

### Phone features

Lines quantity:	6 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y

Full duplex:	Y
Call transfer:	Y
<b>Audio</b>	
Speakerphone:	Y
Voice codecs:	G.711,G.722,G.722.1,G.729ab,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Frequency range:	150 - 7000 Hz
<b>Networking</b>	
Ethernet LAN:	Y
Ethernet LAN interface type:	Fast Ethernet
Ethernet LAN data rates:	10,100 Mbit/s
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Auto diagnostic:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
RJ-9 ports quantity:	1
DC-in jack:	Y
WAN connection type:	RJ-45
<b>Camera</b>	
Built-in camera:	N
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Weight &amp; dimensions</b>	
Width:	190 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g
<b>Certificates</b>	
Safety:	UL 60950-1 , CE Mark , CAN/CSA C22.2 No 60950-1 , EN 60950-1 , IEC 60950-1 , AS/NZS 60950-1
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
<b>Packaging content</b>	
Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.