

Polycom VVX 501 IP phone (2200-48500-025)

12-line, 3.5" TFT, HD Voice, 2xUSB2.0, 2x Ethernet 10/100/1000



Price details:

Price excl. VAT: 165.91 €

Eco fees: 0.30 €

VAT 21 %: 34.90 €

Product details:

Product code: 2200-48500-025

EAN: 0610807846703

Manufacturer: Polycom

201.11 €

* VAT included

PDF generated on: 10 December, 2018

A desktop phone that works for you

The Polycom VVX 500 series business media phone is designed for today's busy managers and knowledge workers. It is a powerful yet intuitive office phone that can keep up with their multitasking and schedule juggling.

Designed for a broad range of UC environments, the VVX 500 series improves productivity through a touch-screen interface. It also serves as an application platform that complements the applications on the user's computer.

Polcom VVX 500 series supports expansion modules for applications such as personal videoconferencing and wireless networking. It is easy to deploy and manage with an enterprise-grade configuration method, so administrators can easily provision and maintain handsets throughout the enterprise.

Designed for enhanced interoperability, Polycom VVX 500 series leverages your existing IT investments by integrating with more IP PBX systems than any other business media phone in the industry.

It offers:

- UC Software and Polycom Desktop Connector to PCs; keyboard and mouse sharing
- Microsoft Exchange calendar integration
- Touch-screen interface
- Expandable accessories for video and wireless
- Open application platform and Web browser
- Simple, flexible and secure provisioning options
- Skype for Business and Office 365 Cloud PBX interoperability (order "Skype for Business Edition" codes ending in "-019")

Main specifications:

Features

| | |
|---|---------------|
| Colour of product: | Black |
| Handset type: | Wired handset |
| Unicode UTF-8 character support: | Y |
| Volume control: | Digital |
| Dual-Tone Multi-Frequency (DTMF) modes: | In-band |
| SIP registrar server: | Y |

Display

| | |
|---------------------|------------------|
| Display: | TFT |
| Display resolution: | 320 x 240 pixels |
| Display diagonal: | 3.5 " |

Phone features

| | |
|-----------------|----------|
| Lines quantity: | 12 lines |
| Call waiting: | Y |

| | |
|------------------------------------|---|
| Distinctive ring: | Y |
| Speed dialing: | Y |
| Call hold: | Y |
| Call forwarding: | Y |
| Conference call: | Y |
| Redialing: | Y |
| Do not disturb function: | Y |
| Call pick up: | Y |
| Full duplex: | Y |
| Call transfer: | Y |
| Audio | |
| Speakerphone: | Y |
| Voice codecs: | G.711,G.722.1,G.729ab,iLBC |
| Noise reduction: | Y |
| Echo cancellation: | Y |
| Voice activity detection: | Y |
| Adaptive jitter buffers: | Y |
| Frequency range: | 150 - 7000 Hz |
| Networking | |
| Ethernet LAN: | Y |
| Ethernet LAN interface type: | Gigabit Ethernet |
| Ethernet LAN data rates: | 10,100,1000 Mbit/s |
| Quality of Service (QoS) support: | Y |
| DHCP client: | Y |
| Event logging: | Y |
| Syslog: | Y |
| Auto diagnostic: | Y |
| Ports & interfaces | |
| Ethernet LAN (RJ-45) ports: | 2 |
| USB 2.0 ports quantity: | 2 |
| RJ-9 ports quantity: | 1 |
| DC-in jack: | Y |
| WAN connection type: | RJ-45 |
| Camera | |
| Built-in camera: | N |
| Power | |
| Power over Ethernet (PoE): | Y |
| Weight & dimensions | |
| Width: | 190 mm |
| Depth: | 180 mm |
| Height: | 150 mm |
| Weight: | 900 g |
| Package width: | 291 mm |
| Package depth: | 97 mm |
| Package height: | 200 mm |
| Package weight: | 1400 g |
| Certificates | |
| Safety: | UL 60950-1 , CE Mark , CAN/CSA C22.2 No 60950-1 , EN 60950-1 , IEC 60950-1 , AS/NZS 60950-1 |
| Operational conditions | |
| Operating temperature (T-T): | 0 - 40 °C |
| Operating relative humidity (H-H): | 5 - 95 % |
| Storage temperature (T-T): | -40 - 70 °C |
| Packaging content | |
| Number of handles included: | 1 pc(s) |
| Quick start guide: | Y |
| Cables included: | LAN (RJ-45) |

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.