

Polycom VVX 601 IP phone (2200-48600-025)

16-line, 4.3" LCD, 16:9, Bluetooth 2.1 EDR, USB 2.0, SIP, 900g



Price details:

Price excl. VAT: 209.18 €

Eco fees: 0.30 €

VAT 21 %: 43.99 €

Product details:

Product code: 2200-48600-025

EAN: 0610807846680

Manufacturer: Polycom

253.47 €

* VAT included

PDF generated on: 15 December, 2018

Enhance productivity and enrich collaboration with the ultimate, all-in-one, one-touch desktop UC solution designed specifically for executives, managers and knowledge workers. The VVX 600 series business media phone delivers a best-in-class personal communications experience with an extensive list of easy-to-use features that complement the way you work. The VVX 600 series is simple for administrators to deploy, maintain and upgrade while seamlessly integrating with third-party productivity applications. Leverage previous IT infrastructure investments and protect your investment into the future with options such as add-on video, wireless and other accessories.

Main specifications:

Features

Colour of product:	Black
Handset type:	Wired handset
Unicode UTF-8 character support:	Y
Plug and Play:	Y
Volume control:	Digital
Dual-Tone Multi-Frequency (DTMF) modes:	In-band
SIP registrar server:	Y

Display

Touchscreen:	Y
Display:	LCD
Display resolution:	480 x 272 pixels
Aspect ratio:	16:9
Display diagonal:	4.3 "
Backlight display:	Y
Touchscreen type:	Capacitive

Phone features

Lines quantity:	16 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y
Full duplex:	Y
Call transfer:	Y

Audio

Speakerphone:	Y
Voice codecs:	G.711,G.722,G.722.1,G.722.1C,G.729ab,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Frequency range:	100 - 20000 Hz
Networking	
Ethernet LAN:	Y
Bluetooth:	Y
Ethernet LAN interface type:	Gigabit Ethernet
Ethernet LAN data rates:	10,100,1000 Mbit/s
Bluetooth version:	2.1+EDR
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Auto diagnostic:	Y
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	2
RJ-9 ports quantity:	1
DC-in jack:	Y
WAN connection type:	RJ-45
Camera	
Built-in camera:	N
Power	
Power over Ethernet (PoE):	Y
Weight & dimensions	
Width:	210 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g
Package width:	291 mm
Package depth:	97 mm
Package height:	200 mm
Package weight:	1400 g
Certificates	
Safety:	UL 60950-1 , CE Mark , CAN/CSA C22.2 No 60950-1 , EN 60950-1 , IEC 60950-1 , AS/NZS 60950-1
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
Packaging content	
Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.