

Polycom VVX 601 IP phone (2200-48600-019)

Business Media Phone, 16 Lines, HD Voice, 2 x Gigabit Ethernet RJ-45, Bluetooth 2.1 EDR, 2 x USB 2.0, 4.3" TFT (480 x 272) Capacitive Touch-Screen



Price details:

Price excl. VAT: 215.91 €

Eco fees: 0.30 €

VAT 21 %: 45.40 €

Product details:

Product code: 2200-48600-019

EAN: 0610807857815

Manufacturer: Polycom

PDF generated on: 13 December, 2018

261.61 €

* VAT included

Enhance productivity and enrich collaboration with the ultimate, all-in-one, one-touch desktop UC solution designed specifically for executives, managers and knowledge workers. The VVX 600 series business media phone delivers a best-in-class personal communications experience with an extensive list of easy-to-use features that complement the way you work. The VVX 600 series is simple for administrators to deploy, maintain and upgrade while seamlessly integrating with third-party productivity applications. Leverage previous IT infrastructure investments and protect your investment into the future with options such as add-on video, wireless and other accessories.

Main specifications:

Features

Product colour:	Black
Handset type:	Wired handset
Expansion module support:	Y
Unicode UTF-8 character support:	Y
Ethernet cable:	Y
Data transfer rate:	1000 Mbit/s
Integrated voicemail:	Y

Display

Touchscreen:	Y
Display:	LCD
Display resolution:	480 x 272 pixels
Aspect ratio:	16:9
Display diagonal:	4.3 "
Touchscreen type:	Capacitive

Phone features

Lines quantity:	16 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y
Full duplex:	Y
Call transfer:	Y

Audio

Speakerphone:	Y
Voice codecs:	G.711,G.722,G.722.1,G.722.1C,G.729ab,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Comfort noise generation (CNG):	Y
Networking	
Ethernet LAN:	Y
Bluetooth:	Y
Bluetooth version:	2.1+EDR
Supported network protocols:	FTP/TFTP/HTTP/HTTPS
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Networking standards:	IEEE 802.1Q,IEEE 802.1p,IEEE 802.1x,IEEE 802.3,IEEE 802.3ab,IEEE 802.3af,IEEE 802.3u
Auto diagnostic:	Y
Ports & interfaces	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	2
RJ-9 ports quantity:	1
Camera	
Built-in camera:	N
Power	
Power over Ethernet (PoE):	Y
Security	
Security algorithms:	802.1x RADIUS,HTTPS,SSL/TLS
Weight & dimensions	
Width:	210 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g
Package width:	291 mm
Package depth:	200 mm
Package height:	97 mm
Package weight:	1400 g
Certificates	
Safety:	UL 60950-1, CE Mark, CAN/CSA-C22.2 No. 60950-1-03, EN 60950-1, IEC 60950-1, AS/NZS 60950-1
Certification:	CNCICASACITCTECMIC/VCCI Class BSIRIMIDANCC 3NOM-121FCC Part 15 (CFR 47) Class BICES-003 Class BEN55022 Class BVCCI Class BEN55024EN61000-3-2; EN61000-3-3TRACUANATEL 3RCM
Compliance industry standards:	ROHS
Skype:	Y
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
Packaging content	
Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.