

# Polycom VVX 301 Skype for Business IP phone (2200-48300-019)

Business Media Phone, 6-Line, HD Voice, 2 x Fast Ethernet RJ-45, 8-Level Grayscale Display (208 x 104), PoE



#### Price details:

Price excl. VAT: 87.59 €

Eco fees: 0.30 €

VAT 21 %: 18.46 €

#### Product details:

Product code: 2200-48300-019

EAN: 0610807857761

Manufacturer: Polycom

**106.35 €**

\* VAT included

PDF generated on: 13 December, 2018

A powerful entry-level Business Media phone for today's cubicle workers

These powerful 6-line entry-level Business Media Phones are for today's cubicle workers that handle a low to moderate volume of calls and need crystal clear communications.

Give your cubicle worker the best experience with this high quality UC Business Media Phone. Designed for a broad range of environments for small and medium businesses.

- Make more efficient and productive calls with the unparalleled voice clarity of Polycom HD Voice
- Improve productivity for cubicle worker's and call center operators through an intuitive easy to use user interface
- Reduce deployment and maintenance costs-the Polycom Zero Touch Provisioning and web based configuration tool makes the VVX 300 series simple to deploy, easy to administer, upgrade, and maintain
- Leverage previous IT infrastructure investments-deploy VVX 300 series business media phones on your existing network without needing to upgrade your call control platform
- Easily to integrate with third- party web-based UC and productivity applications for broad, standards based, open APIs

#### Main specifications:

##### Features

Colour of product:	Black
Handset type:	Wired handset
Expansion module support:	Y
Unicode UTF-8 character support:	Y
Ethernet cable:	Y
Plug and Play:	Y
Data transfer rate:	100 Mbit/s
Integrated voicemail:	Y
Dual-Tone Multi-Frequency (DTMF) modes:	In-band

##### Display

Touchscreen:	N
Display:	LCD
Display resolution:	208 x 104 pixels

##### Phone features

Lines quantity:	6 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y

Call hold:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y
Full duplex:	Y
Call transfer:	Y
<b>Audio</b>	
Speakerphone:	Y
Microphone mute:	Y
Voice codecs:	G.711,G.722,G.722.1,G.729ab,iLBC
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Frequency range:	150 - 7000 Hz
Comfort noise generation (CNG):	Y
<b>Networking</b>	
Ethernet LAN:	Y
Wi-Fi:	N
Bluetooth:	N
Supported network protocols:	FTP/TFTP/HTTP/HTTPS
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Networking standards:	IEEE 802.1Q,IEEE 802.1p,IEEE 802.3,IEEE 802.3ab,IEEE 802.3af,IEEE 802.3u
Auto diagnostic:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
RJ-9 ports quantity:	1
<b>Camera</b>	
Built-in camera:	N
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	802.1x RADIUS
<b>Weight &amp; dimensions</b>	
Width:	190 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g
Package width:	290 mm
Package depth:	200 mm
Package height:	90 mm
Package weight:	1400 g
<b>Certificates</b>	
Certification:	FCC Part 15 (CFR 47) Class BICES-003 Class BEN55022 Class BCISPR22 Class BVCCI Class BEN55024EN61000-3-2; EN61000-3-3NZ TelepermitKorea KC 3UAE TRARussia CUBrazil ANATEL 3Australia RCM
Compliance industry standards:	ROHS
Skype:	Y
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
<b>Packaging content</b>	
Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.