

# Polycom VVX 501 IP phone (2200-48500-019)

Business Media Phone, 12-Line, 3.5" TFT (320 x 240), 2 x Ethernet RJ-45, 2 x USB 2.0



## Price details:

Price excl. VAT: 172.15 €

Eco fees: 0.30 €

VAT 21 %: 36.21 €

## Product details:

Product code: 2200-48500-019

EAN: 0610807857808

Manufacturer: Polycom

**208.66 €**

\* VAT included

PDF generated on: 15 December, 2018

A desktop phone that works for you

The Polycom VVX 500 series business media phone is designed for today's busy managers and knowledge workers. It is a powerful yet intuitive office phone that can keep up with their multitasking and schedule juggling.

Designed for a broad range of UC environments, the VVX 500 series improves productivity through a touch-screen interface. It also serves as an application platform that complements the applications on the user's computer.

Polycom VVX 500 series supports expansion modules for applications such as personal videoconferencing and wireless networking. It is easy to deploy and manage with an enterprise-grade configuration method, so administrators can easily provision and maintain handsets throughout the enterprise.

Designed for enhanced interoperability, Polycom VVX 500 series leverages your existing IT investments by integrating with more IP PBX systems than any other business media phone in the industry.

It offers:

- UC Software and Polycom Desktop Connector to PCs; keyboard and mouse sharing
- Microsoft Exchange calendar integration
- Touch-screen interface
- Expandable accessories for video and wireless
- Open application platform and Web browser
- Simple, flexible and secure provisioning options

Main specifications:

## Features

Colour of product:	Black
Handset type:	Wired handset
Expansion module support:	Y
Unicode UTF-8 character support:	Y
Ethernet cable:	Y
Data transfer rate:	1000 Mbit/s
Integrated voicemail:	Y
Dual-Tone Multi-Frequency (DTMF) modes:	In-band

## Display

Touchscreen:	N
Display:	TFT
Display resolution:	320 x 240 pixels
Aspect ratio:	4:3
Display diagonal:	3.5 "

## Phone features

Lines quantity:	12 lines
Call waiting:	Y
Distinctive ring:	Y
Speed dialing:	Y
Call hold:	Y
Call forwarding:	Y
Conference call:	Y
Redialing:	Y
Do not disturb function:	Y
Call pick up:	Y
Full duplex:	Y
Call transfer:	Y
<b>Audio</b>	
Speakerphone:	Y
Voice codecs:	G.711,G.722,G.722.1,G.722.1C,G.729ab
Noise reduction:	Y
Echo cancellation:	Y
Voice activity detection:	Y
Adaptive jitter buffers:	Y
Comfort noise generation (CNG):	Y
<b>Networking</b>	
Ethernet LAN:	Y
Bluetooth:	N
Supported network protocols:	FTP/TFTP/HTTP/HTTPS
Quality of Service (QoS) support:	Y
DHCP client:	Y
Event logging:	Y
Syslog:	Y
Networking standards:	IEEE 802.1Q,IEEE 802.1p,IEEE 802.1x,IEEE 802.3,IEEE 802.3ab,IEEE 802.3af,IEEE 802.3u
Auto diagnostic:	Y
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	2
RJ-9 ports quantity:	1
<b>Camera</b>	
Built-in camera:	N
<b>Power</b>	
Power over Ethernet (PoE):	Y
<b>Security</b>	
Security algorithms:	802.1x RADIUS,HTTPS,SSL/TLS
<b>Weight &amp; dimensions</b>	
Width:	190 mm
Depth:	180 mm
Height:	150 mm
Weight:	900 g
Package width:	291 mm
Package depth:	200 mm
Package height:	97 mm
Package weight:	1400 g
<b>Certificates</b>	
Safety:	UL 60950-1, CE Mark, CAN/CSA-C22.2 No. 60950-1-03, EN 60950-1, IEC 60950-1, AS/NZS 60950-1
Certification:	CNCICASACITCTECMIC/VCCI Class BSIRIMIDANCC 3NOM-121FCC Part 15 (CFR 47) Class BICES-003 Class BEN55022 Class BVCCI Class BEN55024EN61000-3-2; EN61000-3-3TRACUANATEL 3RCM
Compliance industry standards:	ROHS
Skype:	Y
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Operating relative humidity (H-H):	5 - 95 %
Storage temperature (T-T):	-40 - 70 °C
<b>Packaging content</b>	

Number of handles included:	1 pc(s)
Quick start guide:	Y
Cables included:	LAN (RJ-45)

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.