

## Posbank BOXPOS Q POS terminal (PB-BP1-03HM)

Intel Core i3-2350M Processor, HM motherboard, 4GB SODIMM RAM, SSD 64GB, No OS



### Price details:

Price excl. VAT: 891.07 €

Eco fees: 0.11 €

VAT 21 %: 187.15 €

### Product details:

Product code: PB-BP1-03HM

EAN:

Manufacturer: Posbank

**1,078.33 €**

PDF generated on: 12 December, 2017

Product is discontinued. You can not order it anymore.

\* VAT included

A slimline POS computer that gives needed versatility

The retail hardened BOXPOS Point of Sale bookcase computer offers high performance and extreme durability making it a solid foundation for any custom tailored POS system. BOXPOS boasts a stylish design, small form factor, an industrial grade motherboard and plenty of I/O ports. BOXPOS features and functionally makes it an ideal choice for extreme value.

&#8226; Detachable HDD

&#8226; High performance and built to last

&#8226; Slim & compact space saving design

- Compact design style utilized

- Raid function

- Free expandability

### Main specifications:

#### Processor

Processor frequency:	2.3 GHz
Processor family:	Intel Core i3
Processor model:	i3-2350M
Processor cores:	2
Processor cache:	3 MB
Processor threads:	4
System bus rate:	5 GT/s
Motherboard chipset:	Intel HM76 Express

#### Memory

Internal memory:	4 GB
Internal memory type:	DDR3-SDRAM
Maximum internal memory:	8 GB
Memory slots type:	SO-DIMM
Memory clock speed:	1600 MHz

#### Storage

Total storage capacity:	64 GB
Storage media type:	SSD
Solid-state drive capacity:	64 GB
Solid-state drive interface:	Serial ATA III

#### Graphics

Graphics adapter manufacturer:	Intel
Graphics adapter:	HD Graphics 3000
<b>Networking</b>	
Ethernet LAN:	Y
Ethernet LAN data rates:	10,100,1000 Mbit/s
<b>Ports &amp; interfaces</b>	
Ethernet LAN (RJ-45) ports:	2
USB 2.0 ports quantity:	2
VGA (D-Sub) ports quantity:	1
Line-in:	Y
Line-out:	Y
Microphone in:	Y
Serial ports quantity:	1
PS/2 ports quantity:	1
<b>Design</b>	
Colour of product:	Black
<b>Software</b>	
Operating system installed:	N
<b>Power</b>	
AC input voltage:	24 V
<b>Operational conditions</b>	
Operating relative humidity (H-H):	10 - 80 %
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-20 - 60 °C
<b>Weight &amp; dimensions</b>	
Width:	280 mm
Depth:	355 mm
Height:	78 mm

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.