



WatchGuard Firebox M270 hardware firewall (WGM27001)

8 x 10/100/1000 RJ-45, 1 serial/2 USB, 100 VLAN, DHCP, IPv6, 1Y Standard Support

Price details:

Price excl. VAT: 1,344.82 €

Eco fees: 0.00 €

VAT 21 %: 282.41 €

Product details:

Product code: WGM27001

EAN: 0654522029430

Manufacturer: WatchGuard

PDF generated on: 18 February, 2019



1,627.23 €

Product is discontinued. You can not order it anymore.

* VAT included

Enterprise-Grade Security for Small to Midsize Businesses

Because smaller companies are generally less protected and easier to break into, small business has become the new big target for cyber-attacks. The Firebox M270 and M370 firewalls are specifically engineered to defend all types of small businesses against attacks that are no less fierce than those targeting larger organizations.

Firebox M270 and M370 Unified Threat Management (UTM) solutions are up to 3 times faster than competing products with all security layers turned on, and up to 94 percent faster performing HTTPS inspection, ensuring businesses never have to compromise network security for performance.

Stay Ahead of Evolving Threats

The M270 and M370 are part of WatchGuard's award-winning Firebox security platform. The platform not only provides the most complete suite of unified security controls on the market today, it has consistently been the first to offer solutions for addressing new and evolving network threats including advanced malware and ransomware. Our unique product architecture enables small and midsize businesses to leverage best-in-class security services - from URL filtering and intrusion prevention to application control and ransomware prevention, minus the cost and complexity of multiple single-point solutions.

Always Know What's Happening on Your Network

Interactive, real-time monitoring and reporting through WatchGuard Dimension - included at no additional charge - give an unprecedented view into network security activity so you can take immediate preventive or corrective actions. Over 100 reports and dashboards come standard, including reports for PCI and HIPAA compliance, which means you have one-click access to the data you need to ensure compliance requirements are met.

Quick and Simple Deployment

SMBs usually have smaller, less technical staff, which can make network expansion challenging. With RapidDeploy - a powerful, cloud-based deployment and configuration tool that comes standard with WatchGuard Firebox appliances, all you have to do is power up the appliance at a remote site and connect it to the Internet. The appliance "phones home" and downloads the correct configuration files from the cloud. Just like that.

Easy to Manage

It's in WatchGuard's DNA to deliver advanced network security technologies that were previously thought to be too complex for small and midsize organizations. We take these enterprise-grade technologies and make them easy to manage and deploy. The end result? Small to midsize businesses have one solution, delivering enterprise-grade security, that can be managed from a single-pane-of glass centralized console.

Main specifications:

Data transmission

Firewall throughput: 4900 Mbit/s

Branch Office VPN: 50

Maximum firewall connections per second: 40000

Performance

Built-in processor: Y
Processor family: Intel Atom
Processor cores: 4
Heat dissipation: 256 BTU/h
Concurrent connections: 2000000
Syslog: Y
Mean time between failures (MTBF): 51644 h
Certification: WEEE, RoHS, REACH

Networking

Networking standards: IEEE 802.3ad
Number of users: 500 user(s)
Number of VLANs: 100
DHCP server: Y
DHCP client: Y
Quality of Service (QoS) support: Y
Point-to-point protocol over Ethernet (PPPoE): Y

Security

Security algorithms: 3DES,128-bit AES,256-bit AES,DES,SHA-2
DDoS protection: Y
Deep Packet Inspection (DPI): Y
Stateful Packet Inspection (SPI): Y

Protocols

Management protocols: SNMP v2/v3
Supported network protocols: HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3, SMTP, IMAPS, POP3S, IPv6
Routing protocols: BGP4,OSPF,RIP-1,RIP-2

Management features

Web-based management: Y

Ports & interfaces

Connectivity technology: Wired
USB 3.0 (3.1 Gen 1) Type-A ports quantity: 2
Ethernet LAN (RJ-45) ports: 8
Ethernet LAN data rates: 10,100,1000 Mbit/s
Console port: RJ-45

Memory

Internal memory: 4096 MB

Design

Rack mounting: Y
Form factor: 1U

Power

AC input voltage: 100-240 V
Power consumption (typical): 75 W

Operational conditions

Operating temperature (T-T): 0 - 40 °C
Storage temperature (T-T): -40 - 70 °C
Operating relative humidity (H-H): 10 - 85 %
Operating altitude: 0 - 3000 m
Non-operating altitude: 0 - 4570 m

Weight & dimensions

Dimensions (WxDxH): 438 x 44 x 320 mm

Packaging data

Package width: 560 mm
Package height: 540 mm
Package depth: 130 mm
Package weight: 8500 g

Other features

Safety: NRTL/C, CB
Authentication method: RADIUS, LDAP, VASCO, RSA SecurID, SAML 2.0, SMS

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.