

# WatchGuard Firebox M270 hardware firewall (WGM27071)

Firebox M270 High Availability with 1 Year Standard Support



## Price details:

Price excl. VAT: 676.36 €

Eco fees: 0.00 €

VAT 21 %: 142.04 €

## Product details:

Product code: WGM27071

EAN: 0654522029515

Manufacturer: WatchGuard

PDF generated on: 22 February, 2019



**818.40 €**

Product is discontinued. You can not order it anymore.

\* VAT included

Make your WatchGuard Firebox M270 even more robust with a second High Availability unit for active/passive clustering.

The Firebox M270 High Availability includes 1 year Standard Support for hardware warranty, technical support, and software updates.

The Firebox M270 in short:

- 8 1 Gb ports
- Manage and monitor your device with WatchGuard System Manager, the WatchGuard management servers, and WatchGuard Dimension
- Available with Standard Support, the Basic Security Suite or Total Security

Standard Support includes:

- Hardware warranty
- Unlimited 24x7 technical support
- Software updates
- Threat alerts
- Access to security education resources

## Main specifications:

### Data transmission

Firewall throughput:	4900 Mbit/s
Branch Office VPN:	50
Maximum firewall connections per second:	40000

### Performance

Built-in processor:	Y
Processor family:	Intel Atom
Processor cores:	4
Heat dissipation:	256 BTU/h
Concurrent connections:	2000000
Syslog:	Y
Mean time between failures (MTBF):	51644 h
Certification:	WEEE, RoHS, REACH

### Networking

Networking standards:	IEEE 802.3ad
Number of users:	500 user(s)
Number of VLANs:	100

DHCP server:	Y
DHCP client:	Y
Quality of Service (QoS) support:	Y
Point-to-point protocol over Ethernet (PPPoE):	Y
<b>Security</b>	
Security algorithms:	3DES,128-bit AES,256-bit AES,DES,SHA-2
DDoS protection:	Y
Deep Packet Inspection (DPI):	Y
Stateful Packet Inspection (SPI):	Y
<b>Protocols</b>	
Management protocols:	SNMP v2/v3
Supported network protocols:	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3, SMTP, IMAPS, POP3S, IPv6
Routing protocols:	BGP4,OSPF,RIP-1,RIP-2
<b>Management features</b>	
Web-based management:	Y
<b>Ports &amp; interfaces</b>	
Connectivity technology:	Wired
USB 3.0 (3.1 Gen 1) Type-A ports quantity:	2
Ethernet LAN (RJ-45) ports:	8
Ethernet LAN data rates:	10,100,1000 Mbit/s
Console port:	RJ-45
<b>Memory</b>	
Internal memory:	4096 MB
<b>Design</b>	
Rack mounting:	Y
Form factor:	1U
<b>Power</b>	
AC input voltage:	100-240 V
Power consumption (typical):	75 W
<b>Operational conditions</b>	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	10 - 85 %
Storage relative humidity (H-H):	10 - 95 %
Operating altitude:	0 - 3000 m
Non-operating altitude:	0 - 4570 m
<b>Weight &amp; dimensions</b>	
Dimensions (WxDxH):	438 x 44 x 320 mm
<b>Packaging data</b>	
Package width:	560 mm
Package height:	540 mm
Package depth:	130 mm
Package weight:	8500 g

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.