

Zebra GX430T label printer (GX43-102520-150)

GX430t Thermal Transfer EPL2/ZPL II U



Price details:

Price excl. VAT: 538.21 €

Eco fees: 0.00 €

VAT 21 %: 113.02 €

Product details:

Product code: GX43-102520-150

EAN: 5711783220459

Manufacturer: Zebra

PDF generated on: 19 July, 2018



651.23 €

* VAT included

GX430t Thermal Transfer EPL2/ZPL II USB/Serial/Parallel 64MB/8MB Adj sensor no supplies

Main specifications:

Printing

Print technology:	Thermal transfer
Colour:	N
Maximum resolution:	300 x 300 DPI
Print speed:	102 mm/sec
Maximum print height:	991 mm
Maximum printing width:	104 mm
Standard printer languages:	EPL,EPL2,ZBI,ZPL,ZPL II

Display

Display:	LCD
----------	-----

Ports & interfaces

Ethernet LAN:	Y
Wi-Fi:	N
USB 1.1 ports quantity:	1
Optional connectivity:	Bluetooth,Wireless LAN
Connectivity technology:	Wired
Parallel ports quantity:	1
RS-232 ports:	1

Memory

Internal memory:	8 MB
Flash memory:	64 MB

Paper handling

Maximum label width:	108 mm
Maximum roll diameter:	127 mm
Media thickness:	0.08 - 0.19 mm
Maximum media length:	991 mm
Core diameter:	76 mm

Performance

Built-in barcodes:	1D,2D,AZTECCODE,Code 128 (A/B/C),Code 39,Code 49,Code 93,Data Matrix,EAN128,EAN13,EAN8,GS1 DataBar,Industrial 2/5,Interleaved 2/5,MaxiCode,Micro QR Code,MicroPDF417,PDF417,POSTNET,QR Code,UPC-A,UPC-E
--------------------	---

Number of fonts:	16
Ribbon length:	74 m

Ribbon width:	109.2 mm
Design	
Colour of product:	Black
Power	
Energy Star certified:	Y
AC adapter output voltage:	24 V
Input voltage:	100-240 V
Input frequency:	50-60 Hz
Weight & dimensions	
Width:	193 mm
Depth:	254 mm
Height:	191 mm
Weight:	2100 g
System requirements	
Windows operating systems supported:	Y
Operational conditions	
Operating relative humidity (H-H):	10 - 90 %
Storage relative humidity (H-H):	5 - 95 %
Operating temperature (T-T):	4 - 41 °C
Storage temperature (T-T):	-40 - 60 °C

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.