

# Zebra ZT410 label printer (ZT41046-T4E0000Z)

ZT410 - 24 dot/mm (600 dpi), Rewind (includes Peel), DT/TT, 10/100 Ethernet, USB, Serial, Bluetooth



## Price details:

Price excl. VAT: 2,273.89 €

Eco fees: 0.00 €

VAT 21 %: 477.52 €

## Product details:

Product code: ZT41046-T4E0000Z

EAN: 8718215787976

Manufacturer: Zebra

PDF generated on: 18 March, 2018



# 2,751.41 €

\* VAT included

- Integrated ThingMagic® RFID reader/encoder
- RFID system is available as a factory- or field-installable option
- Prints and encodes tags with a minimum pitch of 0.6"/16 mm
- Supports tags compatible with UHF EPC Gen 2 V1.2/ISO 18000-6C

## RFID Features Continued

- Compliant with Global RFID radio to support multinational deployments
- Adaptive encoding technology automatically eliminates complex RFID placement guidelines
- Variable inlay placement supports a range of inlay positions for maximum media flexibility
- Auto-tag calibration for label lengths of 2" or greater
- Optimized for throughput of both small and large labels
- RFID job-monitoring tools track RFID performance
- Support for industry standard multi-vendor chip-based serialization (MCS)
- Supports block permalocking of user memory compatible with ATA Spec 2000
- RFID ZPL® commands provide compatibility with existing Zebra RFID printers

## More Standard Features

- Construction: Metal frame and Bi-fold metal media cover with enlarged clear viewing window
- Side-loading supplies path for simplified media and ribbon loading
- Element Energy Equalizer (E3) for superior print quality
- Communication - USB 2.0, High-Speed, RS-232 Serial, 10/100 Ethernet, Bluetooth 2.1, USB Host
- Back-lit, multiline graphic LCD display with intuitive menu and easy-to-use keypad for quick operation
- Link-OS
- Bi-colored status LEDs for quick printer status
- ENERGY STAR® qualified

## Main specifications:

### Printing

Print technology:	Thermal transfer
Colour:	N
Maximum resolution:	600 x 600 DPI
Print speed:	356 mm/sec
Maximum printing width:	104 mm

### Display

Display:	LCD
----------	-----

### Ports & interfaces

Ethernet LAN:	Y
Wi-Fi:	N

USB 2.0 ports quantity:	1
RS-232 ports:	1
<b>Paper handling</b>	
Maximum label width:	104 mm
Maximum label length:	0.991 m
Maximum roll diameter:	203 x 76 mm
Media thickness:	0.058 x 0.25 mm
<b>Performance</b>	
Built-in barcodes:	Code 11,Code 128 (A/B/C),Code 39,Code 93,Data Matrix,EAN13,EAN8,MaxiCode,QR Code,TLC39,UPC-A,UPC-E
Ribbon length:	450 m
Ribbon width:	110 mm
<b>Design</b>	
Colour of product:	Grey
<b>Power</b>	
Energy Star certified:	Y
<b>Weight &amp; dimensions</b>	
Width:	269 mm
Depth:	495 mm
Height:	324 mm
Weight:	16330 g
<b>Operational conditions</b>	
Storage temperature (T-T):	-40 - 60 °C

\*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.