

Zebra WT41N0 handheld mobile computer (WT41N0-N2H27ER)

OMAP 4 (1.0 GHz), 512MB RAM, 2GB Flash, 7.112 cm (2.8 ") TFT QVGA (320 x 240), USB Host, IEEE 802.11 a/b/g/n, Bluetooth 2.1+EDR, 4600mAh Li-Ion, IP54, 370g, Black



Price details:

Price excl. VAT: 1,667.12 €

Eco fees: 0.04 €

VAT 21 %: 350.10 €

Product details:

Product code: WT41N0-N2H27ER

EAN:

Manufacturer: Zebra

PDF generated on: 12 December, 2017



2,017.26 €

Product is discontinued. You can not order it anymore.

* VAT included

Arm your workers with advanced, real-time, hands-free mobile computing with the Motorola WT41N0 Wearable Terminal. This rugged device will allow you to achieve maximum error-proof productivity, operational efficiency and accuracy through voice compatibility for streamlined warehouse and package handling functions.

Ergonomic, hands-free wearable design

Award-winning design increases user comfort and productivity.

High-performance next generation platform

Best-in-class dual core processor provides the power to run virtually any enterprise application.

802.11 a/b/g/n WLAN

Easily connects to existing WLAN for fast integration; 802.11n and support for advanced Motorola Solutions' WLAN features greatly improve wireless network bandwidth, performance and reliability, while reducing power consumption and improving voice performance.

Supports text-only, voice-only and combination text and voice applications

Eliminates the effort and cost associated with purchasing and supporting multiple systems for different applications.

Wide temperature range

Designed to operate across a wide temperature ranges ensures operation in virtually all environments of the warehouse, including -4°F/-20°C in freezers (-22°F/-30°C when using freezer pouch).

Secure WLAN communications

Robust support for the latest security protocols keeps your data safe.

2.8" color QVGA display with backlight

Excellent at-a-glance readability in nearly any lighting condition.

Supports Motorola Solutions' RhoMobile best-in-class operation system-agnostic applications

Integrated support for RhoMobile applications allows easy and cost-effective development and deployment of a single application version that runs on practically any device, regardless of operating system or screen size.

Main specifications:

Display

Display diagonal:	2.8 "
Display resolution:	320 x 240 pixels
Touchscreen:	N

Display:	TFT
Memory	
Internal memory:	512 MB
Internal memory type:	RAM
Compatible memory cards:	Not supported
Flash memory:	2048 MB
Processor	
Processor frequency:	1 MHz
Processor family:	Instruments OMAP
Processor manufacturer:	Texas Instruments
Built-in processor:	OMAP 4
GPS Performance	
GPS (satellite):	N
Software	
Operating system installed:	Windows Embedded Compact CE 7.0
Wireless LAN features	
Wi-Fi:	Y
Wi-Fi standards:	802.11a,802.11b,802.11g,802.11n
Data transmission	
Bluetooth:	Y
Data network:	Not supported
Bluetooth version:	2.1+EDR
Camera	
Built-in camera:	N
Audio	
Built-in microphone:	Y
Ports & interfaces	
USB 2.0 ports quantity:	1
Operational conditions	
Storage temperature (T-T):	-40 - 70 °C
Operating relative humidity (H-H):	5 - 95 %
Operating temperature (T-T):	-20 - 50 °C
Power	
Battery capacity:	4600 mAh
Battery technology:	Lithium-Ion (Li-Ion)
Weight & dimensions	
Weight:	369.8 g
Width:	93 mm
Depth:	26 mm
Height:	142 mm
Technical details	
Colour of product:	Black
Phone function:	N
RFID reader:	N
Keyboard layout:	Alphanumeric
International Protection (IP) code:	IP54
Barcode reader:	N

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.