

Zebra MC75A0 handheld mobile computer (MC75A6-PUCSWQRA9WR)

MC75 - 3.5" VGA(640x480), LED, RS-232, 3G WWAN HSDPA, USB 1.1, 3.2MP Camera, Marvell PXA320 806 MHz, 1D Imager, QZ, 256MB/1GB, 802.11a/b/g, Bluetooth IP54, 1.5x, Windows Mobile 6.5



Price details:

Price excl. VAT: 1,418.10 €

Eco fees: 0.04 €

VAT 21 %: 297.81 €

Product details:

Product code: MC75A6-PUCSWQRA9WR

EAN: 0742709357572

Manufacturer: Zebra

PDF generated on: 17 October, 2017



1,715.95 €

* VAT included

The 3.5G MC75A, one of the world's premium EDAs, offers more features and functionality, in a field-proven rugged form factor, than any other device in its class. The turbocharged MC75A addresses business critical mobility needs by maximizing processing power, rugged design, application flexibility, data capture capabilities, connectivity options, security and manageability - all in one device. Two options - 3.5G WWAN/WLAN and WLAN only - enable enterprises to standardize on a single EDA to support workers inside and outside the four walls. Add a field-proven ergonomic design that is easy-to-carry and easy to use, and you have maximum value in a minimum footprint - all at the right price.

Rugged, lightweight design

Meets and exceeds applicable MIL-STD and IEC specifications for drop, tumble and sealing

Powerful microprocessor

Maximizes mobility, giving desktop-like performance with minimal power use

Increased operability

Enabled through Windows® Mobile 6.5 with advanced security, a flexible development platform and improved mobile messaging

3.5G WWAN capability

Delivers high broadband and voice/data performance virtually anywhere in the world

- Connects to most worldwide carriers
- Download speeds of up to 3Mbps
- Integrated voice and data
- Future-proofed and affordable

WLAN and VoIP support

Provides cost-effective connectivity in offices and in hot spots

Assisted and autonomous GPS support

Enables robust location-based applications, boosts signals in weak areas and increasing time to first fix (TTFF)

WPAN and IrDA

Helps connect wirelessly to modems, printers and headsets, as well as legacy business equipment

High definition VGA display

Supports high-resolution images such as high-resolution photographs, video and documents

Backwards compatible with MC70 and MC75 accessories provides investment protection

Multiple keypad options
Includes Numeric, QWERTY, DSD, QWERTZ, and AZERTY keyboards

External WWAN antenna
Improves signal reception and makes connections more dependable

Robust memory space
Supports 256MB RAM; 1GB Flash

Two options
3.5G WAN/LAN and LAN only

FIPS 140-2 Certification and Support
Compliance with the most stringent industry security regulations, including sensitive government applications.

Main specifications:

Display

Display diagonal: 3.5 "
Display resolution: 640 x 480 pixels
Touchscreen: Y

Memory

Internal memory: 256 MB
Internal memory type: RAM
Flash memory: 1024 MB

Processor

Processor frequency: 806 MHz

GPS Performance

GPS (satellite): Y

Software

Operating system installed: Windows Mobile 6.5

Wireless LAN features

Wi-Fi: Y
Wi-Fi standards: 802.11a,802.11b,802.11g

Data transmission

Bluetooth: Y
Data network: 3.5G,HSDPA
Bluetooth version: 2.1+EDR

Camera

Built-in camera: Y
Megapixel: 3.2 MP
Auto focus: Y

Audio

Built-in microphone: Y
Speakers: Y

Ports & interfaces

Interface: USB 1.1, RS-232

Operational conditions

Storage temperature (T-T): -40 - 70 °C
Operating temperature (T-T): -10 - 50 °C
Operating temperature (T-T): 14 - 122 °F

Power

Battery capacity: 3600 mAh
Battery technology: Lithium-Ion (Li-Ion)

Weight & dimensions

Weight: 398 g
Width: 88 mm
Depth: 44 mm

Height: 152.4 mm

Technical details

Colour of product:

Black

Phone function:

Y

RFID reader:

N

Certification:

UL, cUL 60950-1, IEC, EN60950-1, EMI, RFI, FCC 15, ICES 003 B, EN55022 B, 55024, EN60601-1-2, AS/NZS CISPR 2, UL, cUL 60950-1, IEC, EN60950-1, RoHS, FCC 2, FCC OET, RSS-102, EN 50360 2003, EMI/RFI, FCC 15, B, ICES 003 B, EN55022 B, 301 489-1, 301 489-3, EN 301 489-7, EN 301 489-17, EN 301 489-24, EN 60601-1-2, AS/NZS CISPR 22, IEC 2, FDA II, IEC60825-1, EN60825-1

Keyboard layout:

QWERTY

Barcode reader:

Y